



S39927

12T8/LED/36-835/BP/SE-DE

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	12W
Color Temperature:	3500K
Length:	36.00"
Base:	Medium Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	12W
Volts:	120-277V
Shape:	T8
Filament:	LED
Base:	Medium Bi Pin
ANSI Base:	G13
Finish:	Gloss White
Housing Color:	White
Hours Rated:	50000H
Color Temperature:	3500K
CRI:	82CRI
Lumen Output:	1400L

Dimmable:	Non-Dimmable
Beam Spread:	210D
Power Factor:	0.9
Operating Temp:	-20C (-4F) to a maximum of +45C (+113F)
Ballasting Requirements:	Ballast Bypass
Ballast Type:	Type B
Single / Dual End:	Single Ended, Double Ended
Safety Listing:	cULus Classified
Technology:	LED
Material:	Glass

DIMENSIONS

MOL:	36.00"
MOD:	1.1"
Weight:	0.33

LISTINGS

Safety Listing:	cULus Classified
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PLGWY2SBB1MN
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
CEC Terse:	Lawful for sale
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923399275
Each Quantity:	1
Each Dimensions:	36.00 x 1.10 x 1.10"

Case UPC:	10045923399272
Case Quantity:	25
Case Dimensions:	37.00 x 6.00 x 6.00"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2021
Satco Products, Inc.
All Rights Reserved
June 10, 2021