



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11969 - 12.5 Watt T8 LED; CCT Selectable; G13 base; 50000
Average rated hours; Type B; Ballast Bypass; 25PK

- CCT Selectable
- Rated for Enclosed Fixture



ELECTRICAL

Technology:	LED
Watts:	12.5W
Volts:	120V-277V
Lumens:	1700L/1750L/1800L
CRI:	83
CCT (Kelvins):	3000K/3500K/4000K
Temperature:	Warm White to Neutral White
Beam Spread :	220
Hours Rated:	50000
Dimmable:	Non-Dimmable
Fluorescent Equivalent :	32W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballast Bypass/Direct:	Ballast Bypass
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Single Ended, Double Ended
Number of LEDs :	144
THD:	<25
Power Factor :	0.9
Light Source:	LED
Warranty:	5 Year Limited - T8 LED Bulbs

PACKAGING

Each UPC:	045923119699
Each Quantity:	25
Each Dimensions:	50.00 x 6.50 x 6.70
Case UPC:	10045923119696
Case Quantity:	25
Case Dimensions:	50.00 x 6.50 x 6.70

INFO

Additional Info:	Sold in packs of 25
------------------	---------------------

PHYSICAL

ANSI Base:	G13
Base:	Medium Bi Pin
Shape:	T8
Finish:	White
Lens Finish:	Frost
Lens Material:	Glass
MOD (In.):	1.00
MOL (In.):	48.00
Weight (Lbs.):	0.55
Material:	Plastic
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Classified
Location Rating:	Damp
Indoor/Outdoor:	Indoor
Energy Star Qualified:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-L7RWZ3
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
Rated For Enclosed Fixture:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions