



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S13146 - 30 Watt; LED Garage Utility Light; 5000K; Medium base; Adjustable Beam Angle



ELECTRICAL

Technology:	LED
Watts:	30W
Volts:	120V
Lumens:	3000L
CRI:	80
CCT (Kelvins):	5000K
Temperature:	Natural Light
Beam Spread :	100-300
Hours Rated:	50000
Dimmable:	Non-Dimmable
Incandescent Equivalent :	200W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Number of LEDs :	170
Power Factor :	0.9
Light Source:	LED
Warranty:	5 Year Limited - 10 hr per day

PACKAGING

Each UPC:	045923131462
Each Quantity:	1
Each Dimensions:	4.45 x 4.45 x 7.09
Case UPC:	10045923131469
Case Quantity:	24
Case Dimensions:	18.70 x 14.06 x 14.96

PHYSICAL

ANSI Base:	E26
Base:	Medium
Shape:	Multi-Beam
Finish:	White
Lens Material:	Plastic (PS)
MOD (In.):	13.98
MOL (In.):	4.50
Weight (Lbs.):	1.05
Material:	Plastic (PS)
Housing Color:	White

COMPLIANCE

Safety Listing:	cETLus - Classified
Location Rating:	Damp
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	ESID-2398099
Energy Star Lamp Category:	LED Surface Mount Ceiling Retrofit
Enclosure Rating:	Open Rated Lamp
Rated For Enclosed Fixture:	No
FCC Compliant:	Yes
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions



S13146 - 30 Watt; LED Garage Utility Light; 5000K; Medium base; Adjustable Beam Angle

ACCESSORIES



D2103

Display Unit Containing 36 pieces; 30 Watt; LED Garage Utility Light; 5000K; Medium base; Adjustable Beam Angle
