



ELECTRICAL

LLLOTRIOAL	
Technology:	LED
Watts:	65W/32W
Volts:	100V-277V
Lumens:	8450L/4420L
CRI:	80
CCT (Kelvins):	3000K/4000K/5000K
Temperature:	Warm to Cool White
Beam Spread :	280
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	Only dimmable through wattage
	selection switch on lamp. NOT
	dimmable with wall dimmers or
	any other dimming controls.
Incandescent Equivalent :	400W
Fluorescent Equivalent :	150W
HID Equivalent :	175W-250W
Operating Temperature :	-22C (-30F) to +45C (+113F)
Lamp Ballast Type A/B/C:	Туре В
Number of LEDs :	414
Burning Position :	Universal
Surge Protection :	Built-in surge protection - 4KV
Power Factor :	>0.9
Light Source:	LED
Warranty:	5 Year Limited - Hi-Pro

PACKAGING

Each UPC:	045923131660
Each Quantity:	1
Each Dimensions:	5.31 × 5.31 × 9.41
Case UPC:	10045923131667
Case Quantity:	12
Case Dimensions:	21.90 x 16.50 x 10.20

Project/Job Name:

Location:

Fixture Type:

Notes:

S13166 - 65 Watt; A-Plus 37; LED; CCT Selectable and Wattage Selectable; Medium base; Type B; Ballast Bypass; ColorQuick Technology; PowerQuick Technology

- Wattage Selectable
- CCT Selectable
- Rated for Enclosed Fixture











PHYSICAL

ANSI Base:	E26
Base:	Medium
Shape:	AP37
Finish:	White
Lens Finish:	Frost
Lens Material:	Polycarbonate (PC)
MOD (In.):	4.61
MOL (In.):	7.76
Weight (Lbs.):	2.52
Material:	Aluminum
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Damp
Indoor/Outoor:	Indoor and Outdoor
Energy Star Qualified:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions

INFO

Specification Note:	Lumen/Watt/CCT Ratio Chart in Documents.
Min Compartment Size:	Length: 8 in. Width: 8 in. Height: 11 in.