



ELECTRICAL

Technology:	LED
Watts:	18W
Volts:	277V-347V
Lumens:	2340L/2520L/2430L
CRI:	80
CCT (Kelvins):	3000K/4000K/5000K
Temperature:	Warm to Cool White
Beam Spread :	300
Hours Rated:	50000
Dimmable:	Non-Dimmable
HID Equivalent :	70W
Operating Temperature :	-30C (-22F) to +45C (+113F)
Lamp Ballast Type A/B/C :	Туре В
Number of LEDs :	168
Power Factor :	0.9
Light Source:	LED
Warranty:	5 Year Limited - Hi-Pro

PACKAGING

Each UPC:	045923231605
Each Quantity:	1
Each Dimensions:	8.26 x 2.83 x 2.83
Inner UPC:	20045923231609
Inner Quantity:	12
Inner Dimensions:	12.00 x 9.00 x 8.85
Case UPC:	10045923231602
Case Quantity:	24
Case Dimensions:	18.90 x 12.60 x 9.65

Project/Job Name:

Location:

Fixture Type:

Notes:

\$23160 - 18 Watt LED HID Replacement; CCT Selectable; Type B; Ballast Bypass; Medium Base; 277-347 Volt; ColorQuick Technology

• CCT Selectable

• Rated for Enclosed Fixture









PHYSICAL

ANSI Base:	E26
Base:	Medium
Shape:	Corncob
Finish:	White
Lens Finish:	Clear
Lens Material:	Plastic
MOD (In.):	2.36
MOL (In.):	6.22
Weight (Lbs.):	0.57
Material:	Aluminum / Polycarbonate (PC)
Housing Color:	Dark Gray
Sensor:	No

COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Damp
Indoor/Outoor:	Indoor and Outdoor
Energy Star Qualified:	No
UL/ETL File Listing:	CN/US - E356817; CN/US -
	E335148
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP64
NSF Approved:	No
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions

INFO

Min Compartment Size:	Length: 8.46 in. Width: 6.00 in. Height: 6.00 i