



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S23162** - 36 Watt LED HID Replacement; CCT Selectable; Type B; Ballast Bypass; Medium Base; 277-480 Volt; ColorQuick Technology

- CCT Selectable
- Rated for Enclosed Fixture



## ELECTRICAL

Technology:	LED
Watts:	36W
Volts:	277V-480V
Lumens:	4680L/5040L/4860L
CRI:	80
CCT (Kelvins):	3000K/4000K/5000K
Temperature:	Warm to Cool White
Beam Spread :	300
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	ONLY Dimmable Via Sensor Port
HID Equivalent :	175W
Operating Temperature :	-30C (-22F) to +45C (+113F)
Lamp Ballast Type A/B/C :	Type B
Number of LEDs :	224
Power Factor :	0.9
Light Source:	LED
Warranty:	5 Year Limited - Hi-Pro

## PACKAGING

Each UPC:	045923231629
Each Quantity:	1
Each Dimensions:	9.80 x 3.66 x 3.66
Case UPC:	10045923231626
Case Quantity:	12
Case Dimensions:	15.35 x 11.57 x 10.40

## PHYSICAL

ANSI Base:	E26
Base:	Medium
Shape:	Corn-cob
Finish:	White
Lens Finish:	Clear
Lens Material:	Plastic
MOD (In.):	3.35
MOL (In.):	7.73
Weight (Lbs.):	1.40
Material:	Aluminum / Polycarbonate (PC)
Housing Color:	Dark Gray
Sensor:	Optional

## COMPLIANCE

Safety Listing:	cUL - Classified; cRUus - Recognized Component
Location Rating:	Damp
Indoor/Outdoor:	Indoor and Outdoor
Energy Star Qualified:	No
UL/ETL File Listing:	CN - E356817; US/CN - E335148
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP64
NSF Approved:	No
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions

## INFO

Min Compartment Size:	Length: 10.55 in. Width: 8.00 in. Height: 8.00 in.
-----------------------	--

**ACCESSORIES**

---



**80-954** Wifi Control for use with Hi-Pro 360 Lamps

---



**80-955** PIR Motion Sensor for use with Hi-Pro 360 Lamps

---



**80-956** Daylight Sensor for use with Hi-Pro 360 Lamps

---



**80-957** Motion Sensor for use with Hi-Pro 360 Lamps; Microwave Sensor

---