



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S23166 - 54 Watt LED HID Replacement; CCT Selectable; Type B; Ballast Bypass; Mogul Extended Base; 277-480 Volt; ColorQuick Technology

- CCT Selectable
- Rated for Enclosed Fixture



ELECTRICAL

Technology:	LED
Watts:	54W
Volts:	277V-480V
Lumens:	7020L/7560L/7290L
CRI:	80
CCT (Kelvins):	3000K/4000K/5000K
Temperature:	Warm to Cool White
Beam Spread :	300
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	ONLY Dimmable Via Sensor Port
HID Equivalent :	250W
Operating Temperature :	-30C (-22F) to +45C (+113F)
Lamp Ballast Type A/B/C :	Type B
Number of LEDs :	280
Power Factor :	0.9
Light Source:	LED
Warranty:	5 Year Limited - Hi-Pro

PACKAGING

Each UPC:	045923231667
Each Quantity:	1
Each Dimensions:	10.98 x 3.66 x 3.66
Case UPC:	10045923231664
Case Quantity:	12
Case Dimensions:	15.35 x 11.57 x 11.60

PHYSICAL

ANSI Base:	EX39
Base:	Mogul Extended
Shape:	CornCob
Finish:	White
Lens Finish:	Clear
Lens Material:	Plastic
MOD (In.):	3.35
MOL (In.):	9.53
Weight (Lbs.):	1.65
Material:	Aluminum / Polycarbonate (PC)
Housing Color:	Dark Gray
Sensor:	Optional

COMPLIANCE

Safety Listing:	cULus - Classified; cRUus - Recognized Component
Location Rating:	Damp
Indoor/Outdoor:	Indoor and Outdoor
Energy Star Qualified:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-1ESYVO
DLC Primary Use:	Replacement Lamps for Outdoor Pole/Arm-mounted Decorative Luminaires (Type B)
UL/ETL File Listing:	CN/US - E356817; CN/US - E335148
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP64
NSF Approved:	No
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions

INFO

ACCESSORIES



80-954 Wifi Control for use with Hi-Pro 360 Lamps



80-955 PIR Motion Sensor for use with Hi-Pro 360 Lamps



80-956 Daylight Sensor for use with Hi-Pro 360 Lamps



80-957 Motion Sensor for use with Hi-Pro 360 Lamps; Microwave Sensor
