



Project/Job Name:

Location:

Fixture Type:

Notes:

**S23168** - 100 Watt LED HID Replacement; CCT Selectable; Type B; Ballast Bypass; Mogul Extended Base; 277-480 Volt; ColorQuick Technology

• CCT Selectable

• Rated for Enclosed Fixture



## ELECTRICAL

Technology:	LED
Watts:	100W
Volts:	277V-480V
Lumens:	13000L/14000L/13500L
CRI:	80
CCT (Kelvins):	3000K/4000K/5000K
Temperature:	Warm to Cool White
Beam Spread :	300
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	ONLY Dimmable Via Sensor Port
HID Equivalent :	400W
Operating Temperature :	-30C (-22F) to +45C (+113F)
Lamp Ballast Type A/B/C :	Type B
Number of LEDs :	480
Power Factor :	0.9
Light Source:	LED
Warranty:	5 Year Limited - Hi-Pro

## PACKAGING

Each UPC:	045923231681
Each Quantity:	1
Each Dimensions:	12.20 x 5.51 x 5.51
Case UPC:	10045923231688
Case Quantity:	4
Case Dimensions:	12.79 x 11.61 x 11.81

## PHYSICAL

ANSI Base:	EX39
Base:	Mogul Extended
Shape:	CornCob
Finish:	White
Lens Finish:	Clear
Lens Material:	Plastic
MOD (In.):	5.12
MOL (In.):	10.46
Weight (Lbs.):	3.19
Material:	Aluminum / Polycarbonate (PC)
Housing Color:	Dark Gray
Sensor:	Optional

## COMPLIANCE

Safety Listing:	cULus - Classified; cRUus - Recognized Component
Location Rating:	Damp
Indoor/Outdoor:	Indoor and Outdoor
Energy Star Qualified:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-FUS4GO
DLC Primary Use:	Replacement Lamps for Outdoor Pole/Arm-mounted Decorative Luminaires (Type B)
UL/ETL File Listing:	CN/US - E356817; CN/US - E335148
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP64
NSF Approved:	No
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions

## INFO

Min Compartment Size:

SATCO.COM | 800-437-2826

Length: 9.84 in. Width: 9.84 in.

© Satco Products, Inc.  
All rights reserved 2022





**S23168** - 100 Watt LED HID Replacement; CCT Selectable; Type B; Ballast Bypass; Mogul Extended Base; 277-480 Volt; ColorQuick Technology

## ACCESSORIES

---



**80-954** Wifi Control for use with Hi-Pro 360 Lamps

---



**80-955** PIR Motion Sensor for use with Hi-Pro 360 Lamps

---



**80-956** Daylight Sensor for use with Hi-Pro 360 Lamps

---



**80-957** Motion Sensor for use with Hi-Pro 360 Lamps; Microwave Sensor

---