



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S33114 - 80/100/130 Wattage Selectable; LED; Hi-Bay; Type B; Ballast Bypass; Mogul Extended; 4000K; 100V-277V; 250W-400W Metal Halide Replacement

- Rated for Enclosed Fixture



ELECTRICAL

Technology:	LED
Watts:	80W/100W/130W
Volts:	100V-277V
Lumens:	11200L/14000L/18200L
CRI:	80
CCT (Kelvins):	4000K
Temperature:	Cool White
Beam Spread :	120
Hours Rated:	50000
Dimmable:	Non-Dimmable
HID Equivalent :	250W/320W/400W
Operating Temperature :	-25C (-13F) to +50C (+122F)
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
Surge Protection :	Built-in surge protection - 4KV
Light Source:	LED
Warranty:	5 Year Limited - Hi-Pro

PACKAGING

Each UPC:	045923331145
Each Quantity:	1
Each Dimensions:	5.91 x 5.91 x 11.73
Case UPC:	10045923331142
Case Quantity:	6
Case Dimensions:	18.31 x 12.40 x 12.52

INFO

Min Compartment Size:	Length: 15.75 in. Width: 14.96 in.
-----------------------	------------------------------------

PHYSICAL

ANSI Base:	EX39
Base:	Mogul Extended
Shape:	Hi-Bay
Finish:	White
MOD (In.):	5.51
MOL (In.):	9.72
Weight (Lbs.):	2.70
Material:	Aluminum / Plastic

COMPLIANCE

Safety Listing:	cULus - Listed; cULus - Classified
Location Rating:	Damp
Indoor/Outdoor:	Indoor and Outdoor
Energy Star Qualified:	No
UL/ETL File Listing:	CN/US - E335148; CN/US - E356817
Enclosure Rating:	Both
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions