SATCO NUVO

Project Name

_ocation

Prepared By



Notes	
-------	--

www] 05-15-2024 04:42:54

General	
Status	Active
Watts	4.5W
HID Equivalent	35W
Volts	120V
Shape	T6
Base	Bi Pin GY6.35
ANSI Base	GY6.35
Finish	Clear
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	430L
Beam Spread	300
Dimmable	Yes-Dimmable
Hours Rated	25000
Product Category	Tubular
Technology	LED
Electrical	
Operating Frequency	60Hz
Dimming Type	Triac
Diffilling Type	mac
Operating Temperature	-20C (-4F) to +40C (+104F)
Operating Temperature	
Operating Temperature Physical	-20C (-4F) to +40C (+104F)
Operating Temperature Physical MOL	-20C (-4F) to +40C (+104F)
Operating Temperature Physical MOL MOD	-20C (-4F) to +40C (+104F) 1.77 0.65
Operating Temperature Physical MOL MOD Housing Color	-20C (-4F) to +40C (+104F) 1.77 0.65 Clear
Operating Temperature Physical MOL MOD Housing Color Weight (lb.)	-20C (-4F) to +40C (+104F) 1.77 0.65 Clear
Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information	-20C (-4F) to +40C (+104F) 1.77 0.65 Clear 0.02
Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Installation Notes	-20C (-4F) to +40C (+104F) 1.77 0.65 Clear 0.02 Not for use in vapor tight fixtures.
Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Installation Notes Rated For Enclosed Fixture	-20C (-4F) to +40C (+104F) 1.77 0.65 Clear 0.02 Not for use in vapor tight fixtures. Yes
Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Installation Notes Rated For Enclosed Fixture Warranty	-20C (-4F) to +40C (+104F) 1.77 0.65 Clear 0.02 Not for use in vapor tight fixtures. Yes
Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Installation Notes Rated For Enclosed Fixture Warranty Compliance	-20C (-4F) to +40C (+104F) 1.77 0.65 Clear 0.02 Not for use in vapor tight fixtures. Yes 3 Year Limited - Mini LED Pin Base
Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing	-20C (-4F) to +40C (+104F) 1.77 0.65 Clear 0.02 Not for use in vapor tight fixtures. Yes 3 Year Limited - Mini LED Pin Base cETLus - Recognized Component
Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	-20C (-4F) to +40C (+104F) 1.77 0.65 Clear 0.02 Not for use in vapor tight fixtures. Yes 3 Year Limited - Mini LED Pin Base cETLus - Recognized Component Damp
Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating CA T20 / T24 Rationale	-20C (-4F) to +40C (+104F) 1.77 0.65 Clear 0.02 Not for use in vapor tight fixtures. Yes 3 Year Limited - Mini LED Pin Base cETLus - Recognized Component Damp Exempt - Base Not Regulated

Yes

RoHS Compliant

