

Project Name

Location

Prepared By



SATCO S13195

25W/LED/HID/ED28/CCT/EX39/CL

Notes

(revised) 11-22-2024 13:11:05

General

Status	Active
Watts	17W/20.5W/25W
HID Equivalent	50W/70W/100W
Volts	120V-277V
Shape	ED28
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Soft White to Natural Light
CRI	80
Lumens	3100L/3700L/4500L
Beam Spread	360
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	LED HID
Technology	LED
Min Compartment Size	Length: 14.02 in. Width: 8.03 in. Height: 8.03 in.
Ballasting Requirements	Ballast Bypass; Direct wire 120-277V line voltage; No ballast or external driver required

Electrical

Operating Frequency	50/60Hz
Candlepower	250
Dimming Type	Step Dimming
Dimming Note	Only dimmable through wattage selection switch on lamp
Power Factor	>0.9
Operating Position	Universal
Surge Protection	Built-in surge protection - 2KV
THD	<20%
Operating Temperature	-30C (-22F) to +45C (+113F)

Physical

MOL	9.92
MOD	3.58
Weight (lb.)	0.55

Additional Information

Rated For Enclosed Fixture	Yes
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5 Year Limited - Hi-Pro

Compliance

Safety Listing	cETLus - Listed
Location Rating	Wet
DLC Approved	Yes
DLC ID	S-YZF3TT
CA T20 / T24 Rationale	Exempt - Base Not Regulated
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes