

S11655R1 - 24 Watt T5 LED; 35K/4K/5K/65K CCT Selectable; 48 Inch; G5 Base; Type B; PET Coated; Line Voltage; Dimmable; 120-347 Volt



GENERAL

Company	SATCO
EA Height	0.75
EA Width	0.75
EA Length	45.67
Lamp Ballast Type AB	Type B
Dimmable Text	120V only
Material	Plastic
Fixture Type	Linear
Status	Active
Surge Protection	Built-in-surge protection - 0.5KV
Total Harmonic Distortion	<20%
CCT Selectable	True
Wattage Selectable	False
Finish Family	White
Amps	0.200-0.070A
IOT Enabled	False
Lens Finish	Frost
Lens Material	Glass
Nominal Length	48.0
Operating Position	Universal
Power Factor	>0.9
SDS Class	LED_Lamp
Shatter Proof Type	PET Coated
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	54W
Incandescent Equivalent	100W

ELECTRICAL

CCT (Kelvin Temp)	3500K/4000K/5000K/6500K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	180
Color Temp	Neutral White to Daylight
CRI	80+
Dimming Type	Reverse Phase
Operating Frequency	50/60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	3200L
Volts	120V-347V
Watts	24W

PHYSICAL

Lamp Base	Miniature Bi Pin
Finish	Frost
ANSI Base	G5
Lamp Type	T5
MOD Lamps	0.62
MOL	45.75

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	True

PACKAGING

UPC	045923410000
Case Cube	0.5704
Case Height	4.72
Case Length	48.23
Case Quantity	25
Case UPC	10045923410007
Case Weight	9.65
Case Width	4.33
EA Cube	0.0149
EA Height	0.75
EA Length	45.67
EA Quantity	1
EA Weight	0.35
EA Width	0.75
Inner Cube	0.0
Pack Type	Sleeve
Web Length	45.75
Web Width	0.62

COMPLIANCE

CA Regulations	Exempt - Base Not Regulated
Dark Sky Rated	False
FCC Compliant	True
IP Rating	IP20
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cRUus - Recognized Component, cULus - Classified
California Ban	Lawful for sale
Energy Star Certified	No
Title 20	Exempt
T24 Compliant	False