



Job Name:

Job Type:

Comments:

Quantity:

**14602S-15: LED Traverse: 4" LED Recessed 2700K Retrofit/Downlight**

**Dimensions:**

**Diameter:** 5 1/2"

**Mounting Proc.:** Dual Mount

**Height:** 2 1/8"

**Connection:** Both



**Features:**

- The advanced LED technology in Sea Gull Lighting products is carefully designed and selected to consist of the highest quality LED chipsets for superior performance and reliability.

**Material List:**

**Safety Listing:**

cETL Listed

**Instruction Sheets:**

Trilingual (English, Spanish, and French) (HC-1943FS)

**Collection:** Traverse LED and LED Recessed Retrofit

The 4" Traverse LED Downlight delivers the performance of incandescent downlights while reducing energy and operating cost by 80% and requiring virtually no maintenance. Ideal for general lighting in residential and commercial applications, the damp rated Traverse can be used for shower applications as well. The Traverse LED downlight is also an excellent alternative to costly fire rated recessed housings.

While the Traverse draws as few as 10 watts continuously, it could have an in-rush current spike and should therefore be treated as a 80W load when sizing dimmers. The recommended maximum number of 4" Traverse LED units per an approved 600W dimmer is 7 units.

Incredibly easy to install: retro-fits 4" housings or flush mount to a 4" junction box, with a minimum 1.5".

9.5 watts: reduces energy use and operating cost by 80%

425 -450 lumens output is equivalent to 50W PAR 20 halogen lamp

50,000 hour life, lasts 25X's longer than conventional lighting for maintenance free operation

Smooth dimming down to 5%

Soft white light: 2700K color temperature, also available in 3000K color temperature

Color correct illumination: 80 CRI

Sleek aluminum housing is also an ultra efficient heat sink. Maximizes life

of LEDs and improves efficiency

Safe and easier to use. Starts instantly & flicker free, will not fade or discolor illuminated items, contains no mercury and projects no heat into the room.

Innovative design provides the look and feel of recessed without the extra labor and material cost of conventional recessed lighting

UL listed for retrofit use with 4" recessed housings from a variety of manufacturers. Please refer to the Traverse brochure and instruction sheet for complete details

ETL damp location listed, can be used as shower light. Check local codes.

While the Traverse draws as few as 10 watts continuously, it could have an in-rush current spike and should therefore be treated as a 80W load when sizing dimmers. The recommended maximum number of 4" Traverse LED units per an approved 600W dimmer is 7 units.

UPC #:785652215865

Finish: White (15)

### Shade / Glass / Diffuser Details:

Part	Material	Finish	Quantity	Item Number	Length	Width	Height	Diameter	Fitter Diameter	Shade Top Length	Shade Top Width	Shade Top Diameter
Lens	Acrylic	Undefined	1									

### Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	UPS Ship
Individual	14602S-15	1	785652215865	8.125	6	3.75	0.106	1.3	Yes
Master Pack	14602S-15	4	10785652215862	17	8.5	6.75	0.564	5.9	Yes
NJ Pallet		480		48	40	72	80	708	No
NV Pallet		480		48	40	72	80	708	No