



Job Name:

Job Type:

Comments:

Quantity:

96223S-12: 12V Hardwire 60w Zero-Load Electronic Transformer



Dimensions:

Length:	5"
Width:	1 19/32"
Height:	1"

Material List:

Safety Listing:

ETL Listed for Dry Locations

Instruction Sheets:

Trilingual (English, Spanish, and French) (HC-1844FS)

Collection: Ambiance® LED Disk Lighting

UL 2108, hardwire 60w 12v Zero-Load Transformer in Black Finish.
With terminal blocks for permanent in-line wiring.

No minimum load, ideal for shorter runs of Lx LED festoon (or incandescent)

Allows for longer runs without noticeable voltage drop when used with Lx LED festoons, up to 20' from the transformer to the last festoon

UL 2108 approved, flame resistant plastic cases with wiring compartment & integrated strain relief (input side).

Low profile design that mounts neatly out of view (1"H x 1.6"W x 5"L)

Compatible with most standard dimmers including electronic low voltage dimmers (recommended)

Electronic circuit design for increased efficiency & reliability

Short circuit & overload protection, automatic shut down/reset

Emits no audible noise, sound rated A

Maximum operating temperatures -20°C to +90°C

Input 120VAC, output 12VAC 0-60W

High power factor > 95%

ETL listed, dry location

New/improved transformer case/enclosure: An electrically isolated, flame resistant, UL 2108 approved plastic enclosure

UPC #:785652030079

Finish: Black (12)

Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	UPS Ship
Individual	96223S-12	1	785652030079	6.25	1.75	1.25	0.008	0.3	Yes
Master Pack		3	10785652030076	8.5	3	3.75	0.055	1.1	Yes
Shipping Master		10	10785652030076	6.75	6.25	4.25	0.104	3.4	Yes