



100 Bone



150 Silver



500 Grey

Style Number	221TS	220TS	219TS	222TS	238TS
Construction	ceramic	ceramic	ceramic	ceramic	ceramic
Tile Type	floor tile	floor tile	floor tile	bullnose	mosaic
Tile Size	12" x 24"	17" x 17"	13" x 13"	2.75" x 13"	13" x 13" x 2"

Technical

Wear Rating Group	4	4	4	4	4
Break Strength	350 lbs.	350 lbs.	350 lbs.	N/A	N/A
Water Absorption %	3-6	3-6	3-6	3-6	3-6
DCOF	≥ 0.42	≥ 0.42	≥ 0.42	≥ 0.42	≥ 0.42
Shade Variation	V2	V2	V2	V2	V2
Installation Area	Floors, Walls	Floors, Walls	Floors, Walls	Floors, Walls	Floors, Walls

A DCOF value of >0.42 is the new standard for tiles specified for commercial application in standard A137.1-2012, Section 9.6. It replaces the SCOF value of >0.60 referenced in ASTM C1028. For more information on the correlation between the two values and about the DCOF AcuTest visit the Tile Council of North America's website: www.tcnatile.com

MANUFACTURER'S WARNING:

- Tiles with DCOF AcuTest values less than 0.42 are not recommended for use in areas with wet or slippery conditions. If such tiles are used as a walking surface where water, ice, oil, grease and/or other substances are present, such a condition could cause a reduction in foot traction and become unexpectedly slippery resulting in a fall and personal injury. See ANSI standard A137.1 section 6.2.2.1.10, available at www.tcnatile.com/sections6.2.2.1.10.html.
- Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.
- Since there is a shade variation on all natural products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Colors



100 Bone



150 Silver



500 Grey

