

TILE & STONE

DIVA
porcelain



100 White



100 & 500



500 Black

DIVA

Nano sealed — does not require sealing on most normal applications

Uses the chemical method as described above. Suitable for most residential, but commercial may benefit from a sealer application. Sealer recommended if using a high performance or contrasting grout color.

TILE & STONE

Style Number	CS05V	CS04V	CS03V	CS06V	CS07V
Construction	porcelain	porcelain	porcelain	porcelain	porcelain
Tile Type	floor tile polished	floor tile polished	floor tile polished	bullnose polished	mosaic matte
Tile Size	24" x 24	12" x 24"	12" x 12"	3" x 24"	12" x 12" x 2"
Edges	rectified	rectified	rectified	rectified	rectified

Technical

Wear Rating Group	4	4	4	4	4
Break Strength	> 450	> 450	> 450	N/A	N/A
Water Absorption %	≤ 0.5	≤ 0.5	≤ 0.5	≤ 0.5	≤ 0.5
DCOF	< 0.42	< 0.42	< 0.42	< 0.42	> 0.42
Shade Variation	V2	V2	V2	V2	V2

Installation Area Floors, Walls, Exteriors* Floors, Walls, Exteriors* Floors, Walls, Exteriors* Floors, Walls, Exteriors* Floors, Walls, Exteriors*


* exterior wall only

A DCOF value of >0.42 is the new standard for tiles specified for commercial application in standard A137.1-2012, Section 9.6. It replaces the SCOF value of >0.60 referenced in ASTM C1028. For more information on the correlation between the two values and about the DCOF AcuTest visit the Tile Council of North America's website: www.tcnatile.com


MANUFACTURER'S WARNING:

- Tiles with DCOF AcuTest values less than 0.42 are not recommended for use in areas with wet or slippery conditions. If such tiles are used as a walking surface where water, ice, oil, grease and/or other substances are present, such a condition could cause a reduction in foot traction and become unexpectedly slippery resulting in a fall and personal injury. See ANSI standard A137.1 section 6.2.2.1.10, available at www.tcnatile.com/sections6.2.2.1.10.html.
- Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.
- Since there is a shade variation on all natural products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Colors




100 White




500 Black

CS07V matte mosaic



100 White



500 Black

