



200 Drift



270 Quarry



510 Glacier



730 Glade

ROCKWOOD POLISHED

Nano sealed — does not require sealing on most normal applications

Uses the chemical method as described above. Suitable for most residential, but commercial may benefit from a sealer application. Sealer recommended if using a high-performance or contrasting grout color.

TILE & STONE

Style Number	CS53L	CS18Q	CS16W	CS55L	CS54L
Construction	porcelain	porcelain	porcelain	porcelain	porcelain
Tile Type	floor tile matte	floor tile polished	bullnose polished	bullnose matte	mosaic basketweave matte
Tile Size	12" x 24"	12" x 24"	3" x 12"	3" x 12"	12" x 12" x 2"
Edges	—	rectified	rectified	—	—

Technical

Wear Rating Group	4	4	4	4	4
Break Strength	300	300	300	300	300
Water Absorption %	0.5	0.5	0.5	0.5	0.5
DCOF	> 0.42	< 0.42	< 0.42	> 0.42	> 0.42
Shade Variation	V2	V2	V2	V2	V2
Installation Area	Floors, Walls, Exteriors	Floors, Walls, Exteriors*	Floors, Walls, Exteriors*	Floors, Walls, Exteriors	Floors, Walls, Exteriors

*exterior wall only for polished product

A DCOF value of >0.42 is the new standard for tiles specified for commercial application in standard A1371-2012, Section 9.6. It replaces the SCOF value of >0.60 referenced in ASTM C1028. For more information on the correlation between the two values and about the DCOF AcuTest visit the Tile Council of North America's website: www.tcnatile.com

MANUFACTURER'S WARNING:

- Tiles with DCOF AcuTest values less than 0.42 are not recommended for use in areas with wet or slippery conditions. If such tiles are used as a walking surface where water, ice, oil, grease and/or other substances are present, such a condition could cause a reduction in foot traction and become unexpectedly slippery resulting in a fall and personal injury. See ANSI standard A137.1 section 6.2.2.1.10, available at www.tcnatile.com/sections6.2.2.1.10.html.
- Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.
- Since there is a shade variation on all natural products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Colors



200 Drift



270 Quarry



510 Glacier



730 Glade

CS60Q mosaic



200 Drift



270 Quarry



510 Glacier



730 Glade



CLARITY
digital imaging



0.5% or less water absorption