

TILE & STONE

GRAND STRANDS

porcelain | ceramic



100 Gossamer



400 Indigo



900 Corduroy



570 Flax



170 Chenille



200 Poplin



500 Twill

Style Number	CS84W	CS85W	CS69X	CS70X	CS68X
Construction	porcelain made in USA	glossy ceramic made in Italy	porcelain made in USA	glossy ceramic made in Italy	porcelain made in USA
Tile Type	floor	wall	SBN	WBN	mosaic
Tile Size	12" x 24"	4" x 12"	2.75" x 12"	4" x 12"	12" x 12" x 2"

Technical

Wear Rating Group	4	N/A	4	N/A	4
Break Strength	> 250	> 250	> 250	> 250	> 250
Water Absorption %	< 0.5	16	< 0.5	< 0.5	< 0.5
Pre-consumer Recycled Content	31%	N/A	31%	N/A	31%
Post-consumer Recycled Content	9%	N/A	9%	N/A	9%
DCOF	> 0.42	N/A	> 0.42	N/A	> 0.42
Shade Variation	V1	V1	V1	V1	V1
Installation Area	Floors, Walls, Exteriors	Walls	Floors, Walls, Exteriors	Walls	Floors, Walls, Exteriors

A DCOF value of >0.42 is the new standard for tiles specified for commercial application in standard A1371-2012, Section 9.6. It replaces the SCOF value of >0.60 referenced in ASTM C1028. For more information on the correlation between the two values and about the DCOF AcuTest visit the Tile Council of North America's website: www.tcnatile.com

MANUFACTURER'S WARNING:

- Tiles with DCOF AcuTest values less than 0.42 are not recommended for use in areas with wet or slippery conditions. If such tiles are used as a walking surface where water, ice, oil, grease and/or other substances are present, such a condition could cause a reduction in foot traction and become unexpectedly slippery resulting in a fall and personal injury. See ANSI standard A1371 section 6.2.2.110, available at www.tcnatile.com/sections6.2.2.110.html.
- Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.
- Since there is a shade variation on all natural products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A1371 standards.

Colors




100 Gossamer



170 Chenille



200 Poplin




400 Indigo (Wall & WBN Only)



500 Twill



570 Flax



900 Corduroy



CLARITY
digital imaging



MADE IN THE USA

