



500 Pewter



700 Toast



550 Coal



100 Shell

**Polished product is not pre-sealed and requires sealing prior to and again after grouting.

Style Number	CS90Q	CS91Q	CS89Q	CS92Q	CS93Q	CS94Q	CS95Q
Construction	porcelain	porcelain	porcelain	porcelain	porcelain	porcelain	porcelain
Tile Type	floor tile polished**	floor tile matte	floor tile matte	floor tile matte	bullnose polished**	bullnose matte	basketweave mosaic matte
Tile Size	12" x 24"	12" x 24"	18" x 36"	6" x 36"	3" x 12"	3" x 12"	12" x 12" x 2"
Edges	rectified	—	rectified	rectified	—	—	—

Technical

Wear Rating Group	4	4	4	4	4	4	4
Break Strength	> 292 lbs.	> 292 lbs.	> 292 lbs.	> 292 lbs.	> 292 lbs.	> 292 lbs.	> 292 lbs.
Water Absorption %	≤ 0.5	≤ 0.5	≤ 0.5	≤ 0.5	≤ 0.5	≤ 0.5	≤ 0.5
DCOF	< 0.42	≥ .5	≥ 0.5	≥ 0.5	< 0.42	≥ 0.5	≥ 0.5
Shade Variation	V2	V2	V2	V2	V2	V2	V2
Installation Area	Floors, Walls, Exteriors*	Floors, Walls, Exteriors	Floors, Walls, Exteriors	Floors, Walls, Exteriors	Floors, Walls, Exteriors*	Floors, Walls, Exteriors	Floors, Walls, Exteriors

* exterior wall only for polished product

A DCOF value of >0.42 is the new standard for tiles specified for commercial application in standard A1371-2012, Section 9.6. It replaces the SCOF value of >0.60 referenced in ASTM C1028. For more information on the correlation between the two values and about the DCOF AcuTest visit the Tile Council of North America's website: www.tcnatile.com

MANUFACTURER'S WARNING:

- Tiles with DCOF AcuTest values less than 0.42 are not recommended for use in areas with wet or slippery conditions. If such tiles are used as a walking surface where water, ice, oil, grease and/or other substances are present, such a condition could cause a reduction in foot traction and become unexpectedly slippery resulting in a fall and personal injury. See ANSI standard A1371 section 6.2.2.110, available at www.tcnatile.com/sections6.2.2.110.html.
- Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.
- Since there is a shade variation on all natural products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A1371 standards.


Colors




100 Shell



500 Pewter



550 Coal



700 Toast

CS95Q mosaic 12" x 12" x 2"



100 Shell



500 Pewter



550 Coal



700 Toast

