## HARDWOOD

#### **CASTLEWOOD OAK**

Engineered







### CASTLEWOOD OAK

# HARDWOOD

	US Units	Metric Units
Style Number	SW485	
Construction	Engineered	
Species	White Oak	
Nominal Overall Thickness	9/16"	14 mm
Nominal Width	7.48"	189.99 mm
Finish	UV Aluminum Oxide	
Gloss Level	10%	
Surface Texture	Wirebrushed	
Edge Description	Micro Bevel	
End Description	Micro Bevel	
Profile	Tongue And Groove	
Weight per Carton	56.22 lbs	25.5 kg
SQFT per Carton	31.09 sq ft	2.88 sq m
SQFT per Pallet	1243.6 sq ft	115.53 sq m
Installation Methods	Nail, Staple, Glue, Floating	
Installation Grade	Above, On, Below	
Variation	High	
GREENGUARD® Certified	Yes	
Cradle-to-Cradle Certified	Yes	
Radiant Heat Approved	Yes	
Residential Warranty	50 Years	
Commercial Warranty	5 Year Commercial	
All measurements are nominal.	Cartons may include random lengths.	

#### **Features**

The Castlewood collection has an abundance of the natural charm that makes hardwood floors so desirable. Creating its stunning character are stylish 7 1/2" widths, extremely handsome linear graining, and sawn face veneers that closely resemble solid hardwood.Castlewood's colors are visually rich - with the beautiful knots, mineral streaks, and natural splits seen in heirloom woods. Heightening its appeal is a very low-gloss finish, which calls to mind vintage European oil-rubbed floors.

**Trim Pieces** length: 78" (\*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are nonstocking - but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



