


HARDWOOD

BROOKSVILLE
Engineered




460 Surfside




493 Bayfront



529 Oceanside



627 Burnside



698 Conway



1023 Crescent Beach



2022 Parasail



5034 Windsurf

	US Units	Metric Units
Style Number	SW492	
Construction	Engineered	
Species	Birch	
Nominal Overall Thickness	3/8"	9.5 mm
Nominal Width	5"	127 mm
Finish	UV Aluminum Oxide	
Gloss Level	20%	
Surface Texture	Smooth	
Edge Description	Micro Bevel	
End Description	Micro Bevel	
Profile	Tongue And Groove	
Weight per Carton	36.71 lbs	16.65 kg
SQFT per Carton	29.53 sq ft	2.74 sq m
SQFT per Pallet	1181.2 sq ft	109.73 sq m
Installation Methods	Nail, Staple, Glue, Floating	
Installation Grade	Above, On, Below	
Variation	Moderate	
GREENGUARD® Certified	Yes	
Cradle-to-Cradle Certified	Yes	
Radiant Heat Approved	Yes	
Residential Warranty	50 Years	
Commercial Warranty	5 Year Commercial	
All measurements are nominal.	Cartons may include random lengths.	

Features

Finish is important with this engineered birch style. Its smooth surfaces sophisticated and refined—perfect for urban and contemporary settings. And the low gloss gives an oil-rubbed appearance, a flooring characteristic that's trending strongly. Fashionable colors nicely set off the moderately defined, subtle birch grain. Made with a 6-ply plywood core, planks have micro-beveled ends and edges and come in random lengths — 13" x up to 47 1/4".

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking - but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)




SFR38

Flush Reducer



SOR38

*Overlap Reducer



SFS38

Flush Stairnose



SSO38

*Overlap Stairnose



SCR38

Threshold / Carpet Reducer



TMD78

T-Molding



QTR96

Quarter Round