


HARDWOOD

GAZEBO OAK Engineered



143 Rustic Natural




401 Saddle



543 Weathered



609 Gunstock



947 Cherry



958 Coffee Bean

	US Units	Metric Units
Style Number	SW515	
Construction	Engineered	
Species	Red Oak	
Nominal Overall Thickness	1/2"	12 mm
Nominal Width	3.5"	88.9 mm
Finish	UV Aluminum Oxide	
Gloss Level	20%	
Surface Texture	Smooth	
Edge Description	Micro Bevel	
End Description	Micro Bevel	
Profile	Tongue And Groove	
Weight per Carton	46.3 lbs	21 kg
SQFT per Carton	27.88 sq ft	2.59 sq m
SQFT per Pallet	1003.68 sq ft	93.24 sq m
Installation Methods	Nail, Staple, Glue, Floating	
Installation Grade	Above, On, Below	
Variation	Moderate	
GREENGUARD® Certified	Yes	
Cradle-to-Cradle Certified	Yes	
Radiant Heat Approved	Yes	
Residential Warranty	50 Years	
Commercial Warranty	5 Year Commercial	
All measurements are nominal.	Cartons may include random lengths.	

Features

Offering classic styling and a smooth modern surface, Gazebo Oak hardwood flooring strikes a nice balance between customer appeal and excellent value.

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking - but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



SFR15
Flush Reducer



SRO15
*Overlap Reducer



SFS15
Flush Stairnose



SSO15
*Overlap Stairnose



SCR15
Threshold / Carpet
Reducer



SWTM5
T-Molding



SQTR5
Quarter Round