HARDWOOD

EMPIRE OAK

engineered





EMPIRE OAK



Style Number	SW583
Construction	Engineered
Thickness	1/2" (12mm)
Width	5"
Species	White Oak
Texture	Wire Brushed
Gloss Level	7%
Janka Hardness Rating	1360
Edge Description	Microbeveled
End Description	Microbeveled
SF per carton	29.53
SF per pallet	1,417.44
Installation	Nail, Staple, Glue, Float
Variation	High
GREENGUARD® Certified	Yes
Radiant Heat Approved	Yes (floating floors only)
Warranty	50 year
All measurements are nominal.	Cartons may include random lengths.

Features

- Wire brushed white oak planks with a matte finish and neutral color palette create a sophisticated urban design.
- Sliced face veneers create clean, linear wood grain for a premium visual.
- Colors Astor, Cabot, Carnegie, Morgan and Roosevelt are also available in Fifth Avenue Oak Herringbone for unique pattern installations.

Sundry Recommendations

Style #	Style Name	Coverage	Moisture	Additional Features		
ADHESIVES						
HS105	35MC — Urethane	35 SF / gal for moisture	No moisture test required	Sound control & crack suppressant		
		60 SF / gal as adhesive	Up to 5 lbs. or 85% RH			
111SA	3-in-1 Ultra — MS	35 SF / gal for moisture	No moisture test required	Sound control & crack suppressant		
		70 SF / gal as adhesive	Up to 5 lbs. or 85% RH			
SWADH	UreBond Plus	35 SF / gal for moisture	Up to 8 lbs. or 85% RH			
		60 SF / gal	Up to 5 lbs. or 85% RH			

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking — but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)









SSH12 SOSH2
Flush Stairnose *Overlap Stairnose



SCH12 Threshold / Carpet Reducer



TMH78 T-Molding



QTR96 Quarter Round

