## HARDWOOD

COUTURE OAK Engineered



shawfloors.com



## **COUTURE OAK**

## HARDWOOD

	US Units	Metric Units
Style Number	SW689	
Construction	Engineered	
Species	White Oak	
Nominal Overall Thickness	1/2"	12 mm
Nominal Width	7.5"	190.5 mm
Finish	UV Aluminum Oxide	
Gloss Level	7%	
Surface Texture	Wirebrushed	
Edge Description	Micro Bevel	
End Description	Micro Bevel	
Profile	Tongue And Groove	
Weight per Carton	51.7 lbs	23.45 kg
SQFT per Carton	31.08 sq ft	2.88 sq m
SQFT per Pallet	1398.6 sq ft	129.93 sq m
Installation Methods	Nail, Staple, Glue, Floating	
Installation Grade	Above, On, Below	
Variation	High	
GREENGUARD® Certified	Yes	
Cradle-to-Cradle Certified	Yes	
Radiant Heat Approved	Yes	
Residential Warranty	50 Years	
All measurements are nominal.	Cartons may include random lengths.	

**Trim Pieces** length: 78" (\*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are nonstocking - but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



