

Shaw 35MC Moisture Control Urethane Adhesive
HS105



- Premium urethane wood flooring adhesive
- Ultimate moisture & sound control
- Ideal for high moisture content slabs
- Low odor - negligible VOC
- Excellent green strength
- 35 s.f./gal with enclosed trowel blade
- Up to 90% RH – 15 lbs Calcium Chloride
- 4 gallon pail

Shaw 4-n-1 Ultra Adhesive
HS091



- Premium urethane wood flooring adhesive
- Moisture and sound control
- Crack suppressant
- Low odor - "0" VOC
- CRI Certified for Indoor Air Quality (IAQ)
- 35 s.f./gal for moisture/sound – 60 s.f./gal as adhesive only
- Up to 90% RH – 15 lbs Calcium Chloride
- 4 gallon pail

Shaw 3-n-1 MS Adhesive
HS097



- Premium MS+ wood flooring adhesive
- Moisture and sound control
- Crack suppressant
- Low odor, low VOC
- Greenguard® Certified for indoor air quality
- 35 s.f./gal for moisture/sound – 70 s.f./gal as adhesive only
- Up to 90% RH - 10 lbs. Calcium Chloride
- 4 gallon pail

Shaw UreBond Plus Urethane Adhesive
SWADH



- Urethane wood flooring adhesive
- Concrete moisture control option
- Warranty up to 8 lbs of moisture vapor transmission and up to 80% RH
- Superior coverage — 35 s.f./gal for moisture — 60 s.f./gal as adhesive only
- Low odor – VOC compliant
- For on, above or below grade
- Non-slumping
- Up to 80% RH — 8 lbs Calcium Chloride
- Spreads easily
- 60 s.f./gal
- 4 gallon pail

Shaw 70 Adhesive
HS096



- Premium resin based wood flooring adhesive
- Easy clean up
- Immediate wet grab with excellent green strength
- Good re-bond properties
- Low odor, low VOC
- Greenguard® Certified for IAQ
- 60 - 70 s.f./gal spread rate
- 4 gallon pail

Shaw EcoMade Adhesive
HS090



- Premium resin based wood flooring adhesive
- Spreads easily
- Good re-bond properties
- Easy clean up
- Low odor, "0" VOC
- Non-slumping
- 60 s.f./gal spread rate
- 4 gallon pail

Shaw Tongue and Groove Adhesive
TNGAD



- Formulated for floating installations
- Clear, fast drying, strong, rapid bond within 24 hours
- Easy clean up
- Non-toxic, non-flammable & solvent free
- 80 - 100 s.f./16 oz. spread rate
- 16 oz. bottle

Shaw Industries, Inc. warrants the use of all Shaw branded Hardwood, Vinyl and Luxury Vinyl adhesives under any manufacturer's products over approved subfloors following proper installation procedures. Contact Shaw Industries for complete details.

RESILIENT FLOORING ADHESIVES

Shaw Kwik Flash LV

080VS - 4gal
081VS - 1gal



- LVP / LVT Adhesive
- Firm setting transitional adhesive
- Faster flash time
- California SCAQMD Rule 1168

- 140 – 225 s.f. / gal spread rate
- Up to 85% RH
- 1 and 4 gallon pails

Shaw 200

026VS - 4gal
052VS - 1gal



- LVP / LVT Adhesive
- Firm setting transitional adhesive
- Extended flash time for large installations
- Greenguard Certified

- 140 – 225 s.f. /gal spread rate
- Up to 85% RH
- 1 and 4 gallon pails

Shaw SI 50

069VS - unit
029VS - roll



- LVP / LVT, carpet tiles and fiberglass backed sheet goods adhesive
- Commercial grade with under bed warranty on approved sheet goods
- Fast easy spray application

- Outstanding water resistance when dry
- “0” VOC
- Up to 150 s.f. per can
- Up to 90% RH
- 22 oz. spray can

Shaw Cove Base

133VS - 4gal
134VS - 1gal
135VS - 30oz. tube



- Rubber & vinyl cove base
- Exceptional wet grab
- Easy clean up
- Low Odor, "0" VOC

- 1 & 4 gallon pail
(220 - 240 l.f./gal)
or 30 oz. Tube
(50-60 l.f. per tube)

Shaw 4100

312VS - 4gal
073VS - 1gal



- LVP / LVT, and fiberglass backed sheet goods adhesive
- Commercial grade with under bed warranty on approved sheet goods
- Packaged in environmentally friendly “EcoBox”
- Premium high strength adhesive

- “0” VOC
- 175 – 225 s.f. /gal spread rate
- Up to 87% RH
- 1 gal pail and 4 gallon box

Shaw 350

4 Gallon

024VS - roll
064VS - unit

1 Gallon

053VS - roll
065VS - unit



- Pressure sensitive residential fiberglass backed sheet goods adhesive
- CRI Green Label Plus Certified
- 300 – 400 s.f. /gal spread rate
- Up to 85% RH
- 1 and 4 gallon pails

Shaw 4062

025VS - roll
068VS - unit



- Premium seam sealer for fiberglass sheet goods
- High strength / fast grab
- Commercial and residential use
- CRI Green Label Plus Certified
- Up to 225 linear feet per 8 oz
- 8 oz bottle

Shaw RV1000
140VS



- Installer friendly
- Fast, easy application
- Economical installation system
- Low odor, non-flammable
- No solvents - "0" VOC

MISCELLANEOUS

Array Grout

055VS

A pre-mixed, ready to use sanded grout for LVT. Available in 12 stylish colors designed to complement any Luxury Vinyl product.



- Smooth Texture
 - Easy Clean-up
 - Flexible — Acrylic Formula
 - Crack Resistant
 - Freeze Thaw Stable
 - 1 gal pail
 - Resort Versailles Coverage Approximately 300s.f./gal.
 - Coverage
- | Joint Width | Per Gallon |
|-------------|------------|
| 1/16" | 500 s.f. |
| 1/8" | 300 s.f. |
| 1/4" | 140 s.f. |

Shaw 9050

905VS - unit



- Multi-Function floor primer
- Easy roll on application
- Ideal for concrete, plywood, floor patch and other porous surfaces
- pH blocker neutralizes excess alkali to safe 5-9 range