



7089 Wild Dunes

	US Units	Metric Units
Style Number	0278V	
Construction	SPC	
Profile	Fold-N-Tap	
Size	7" x 48"	17.78 cm x 121.92 cm
Overall Thickness	0.197"	5 mm
Wear Layer Thickness	12 mil (0.012")	0.3 mm
Attached Underlayment	EVA Pad	
Attached Underlayment Thickness	0.039"	1 mm
Finish	ArmourBead [®]	
Edge Description	Accent Bevel	
Area per Carton	18.91 sq ft	1.76 sq m
Area per Pallet	1512.8 sq ft	140.54 sq m
Installation	Floating	
Installation Grade	Above, On, Below	
FloorScore Certified	Yes	
Residential Warranty	30 Years Residential Resilient Limited Warranty - Defects, Wear, Waterproof, Petproof	
Commercial Warranty	7 Year Light Commercial	
Radiant Panel (ASTM E648)	Passes, Class I	


Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Colors






Coordinating Trim




Baby Threshold*

BT3HS | 94"
 VSBTH | 94"
 VSBT2 | 94"



T-Molding*

TM3HS | 94"
 VSTM6 | 94"



Multi-Purpose Reducer

RD3HS | 94"
 VSMPR | 94"
 VSMP6 | 94"



Quarter Round

QTRHS | 94"
 VSQTR | 94"
 VSQT6 | 94"





Flush Stairnose

FS4HS | 94"
 VFSN2 | 94"

*Packaged with molding track

Coordinating Metal Trim



Finish

Reducer

T-Mold

Stair Cap

Satin Silver

143SA

146SA

140SA

Satin Nickel

144SA

147SA

141SA

Installation Range

Profile Size

Installation Range

3.5mm	1.5mm to 3.5mm heights
5.5mm	3.6mm to 5.5mm heights
8mm	6mm to 8mm heights

Paladin Plus

Coordinating Stair Treads



Stair Tread	TR1HS
White Riser	LVWRI*

*packages of 3

