TILE & STONE GEMSTONE 12X24 POLISHED

glazed color body porcelain



shawfloors.com



Style Number	338TS
Construction	Porcelain
Tile Type	Floor
Tile Size	11.73" x 23.58" 29.8 cm x 59.9 cm
Edges	Rectified
Commercial Warranty	1 YEAR LIMITED
Installation Area	Exteriors, Floors, Walls
Technical	
Wear Rating Group	3
Break Strength	400
Water Absorption %	0.50

DCOF

A DCOF value of > 0.42 is the new standard for tiles specified for commercial application in standard A137.1-2012, Section 9.6. It replaces the SCOF value of > 0.60 referenced in ASTM C1028. For more information on the correlation between the two values and about the DCOF AcuTest visit the Tile Council of North America's website: www.tcnatile.com

MANUFACTURER'S WARNING:

- Tiles with DCOF AcuTest values less than 0.42 are not recommended for use in areas with wet or slippery conditions. If such tiles are used as a walking surface where water, ice, oil, grease and/or other substances are present, such a condition could cause a reduction in foot traction and become unexpectedly slippery resulting in a fall and personal injury. See ANSI standard A137.1 section 6.2.2.1.10.
- Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.
- Since there is a shade variation on all natural products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Colors



100 White



152 Ivory

0.42



200 Beige

550 Dark Grey







