

TILE & STONE

SERENE 24X24 MATTE

glazed porcelain



500 Acero

Style Number	357TS
Construction	Porcelain
Tile Type	Floor
Tile Size	24.13" x 24.13" 61.3 cm x 61.3 cm
Edges	Rectified
Commercial Warranty	1 YEAR LIMITED
Installation Area	Exteriors, Floors, Walls
Technical	
Wear Rating Group	5
Break Strength	250
Water Absorption %	0.50
DCOF	0.42

A DCOF value of > 0.42 is the new standard for tiles specified for commercial application in standard A137.1-2012, Section 9.6. It replaces the SCOF value of > 0.60 referenced in ASTM C1028. For more information on the correlation between the two values and about the DCOF AcuTest visit the Tile Council of North America's website: www.tcnatile.com

MANUFACTURER'S WARNING:

- Tiles with DCOF AcuTest values less than 0.42 are not recommended for use in areas with wet or slippery conditions. If such tiles are used as a walking surface where water, ice, oil, grease and/or other substances are present, such a condition could cause a reduction in foot traction and become unexpectedly slippery resulting in a fall and personal injury. See ANSI standard A137.1 section 6.2.2.1.10.
- Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.
- Since there is a shade variation on all natural products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Colors




100 Cristal



121 Golden Calacata



150 Bianco Covellano



500 Acero

