





295 Chatter Oak




296 River Bend Oak




297 Mineral Maple



915 Dark Elm




1023 Beach Oak



5077 Clean Pine



5078 Greige Walnut



7061 Highlight Oak



7062 Grey Chestnut



7063 Accent Pine



Style Name	Ardent	
Style Number	5606V	
Construction	SPC Rigid Plank	
Class / ASTM F1700	Class III Printed Film Vinyl Tile, Type B (embossed)	
Attached Underlayment	Attached Pad	
Finish	ExoGuard®	
Locking System	Drop/Lock	
	U.S.	Metric
Nominal Dimensions	7 in w, 48 in l	18 cm w, 122 cm l
Actual Dimensions	6.93 in w, 48.03 in l	17.6 cm w, 122 cm l
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Thickness	0.173 in	4.4 mm
Installation	Floating	
Recommended / Required Adhesive	Shaw T 180	



Packaging

Pieces per box	12 pcs	
Area per box	27.73 sq ft	2.58 sq m
Weight per box	41.31 lbs	18.74 kg

Recommended Installation Method



Stagger

Warranties

Resilient 15 Year Commercial Limited

Environmental

Recycled Content **Pre-consumer - 0%, Post-consumer - 0%**

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.