




100 Bone




105 Antler




110 Ecu




200 Patina




500 Mineral




505 Samovar



510 Jasper



515 Cast Ore




520 Gunmetal




705 Nomadic



700 Serengeti



705 Nomadic



710 Sedona



715 Marron



720 Urbane Khaki

Style Name	Purview SPC Click	
Style Number	5613V	
Construction	SPC Rigid Plank	
Class / ASTM F1700	Class III Printed Film Vinyl Tile, Type B (embossed)	
Attached Underlayment	Attached pad	
Finish	ExoGuard+®	
Locking System	5G Lock & Fold	
	U.S.	Metric
Nominal Dimensions	7 in w, 48 in l	18 cm w, 122 cm l
Actual Dimensions	7 in w, 48 in l	17.78 cm w, 121.92 cm l
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Thickness	0.197 in	5 mm
Installation	Floating	
Recommended / Required Adhesive	Shaw 4100 or 4151	



Packaging

Pieces per box	9 pcs	
Area per box	21.25 sq ft	197 sq m
Weight per box	34 lbs	15.42 kg

Recommended Installation Method



Stagger

Warranties

Resilient SPC 15 Year Commercial Limited Warranty

Environmental

Indoor Air Quality	FloorScore® Certified
Recycled Content	Pre-consumer - 0%, Post-consumer - 0%

Specifications are subject to nominal manufacturing variance.
Material supply and/or manufacturing processes may necessitate changes without notice.

