

Style Name	Strie	
Style Number	3305V	
Construction	Heavy Commercial Luxury Vinyl Tile	
Class / ASTM F1700	Class III Printed Film Vinyl Tile, Type B (embossed)	
Attached Underlayment	No	
Finish	ExoGuard+®	
	U.S.	Metric
Nominal Dimensions	9 in w, 60 in l	23 cm w, 152.5 cm l
Actual Dimensions	9 in w, 60 in l	22.86 cm w, 152.4 cm l
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Thickness	0.098 in	2.5 mm
Installation	Direct Glue	


Packaging

Pieces per box	12 pcs	
Area per box	45 sq ft	418 sq m
Weight per box	38.58 lbs	17.5 kg


Recommended Installation Method



Ashlar



Brick



Herringbone



Random



Stagger

Performance Testing

Static Load (ASTM F970)	Passes (Modified), *1000 lbs
Residual Indentation (ASTM F1914)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

Commercial Limited Underbed Bond Warranty S150/4151/LokWorx+ Resilient
Resilient 15 Year Commercial Limited

Environmental

Indoor Air Quality	FloorScore® Certified
Recycled Content	Pre-consumer - 0%, Post-consumer - 0%

Specifications are subject to nominal manufacturing variance.

Material supply and/or manufacturing processes may necessitate changes without notice.

