# Color Scope 3O







## Color Scope 30



Color Scope 30 Style Name

5040V Style Number

Construction Heavy Commercial Luxury Vinyl Tile

Class III Printed Film Vinyl Tile, Type B (embossed) Class / ASTM F1700 NO

Attached Underlayment

Finish ExoGuard+®

> U.S. Metric

Nominal Dimensions 6 in w, 48 in I 15 cm w, 122 cm l Actual Dimensions 5.96 in w, 48 in I 15.14 cm w, 121.92 cm |

Wear Layer Thickness 30 mil (0.03 in) 0.76 mm Overall Thickness ni 8rto 3 mm

Installation Direct Glue

Recommended / Required Adhesive LokWorx+ (236MM) or S150 (5025M)

Packaging

Pieces per box 18 pcs

35.76 sq ft Area per box 3.32 sq m 33.3 lbs Weight per box 15.1 kg

#### Recommended Installation Method











Herringbone

Stagger

### Performance Testing

Static Load (ASTM F970) Passes (Modified), \*1500 lbs

Residual Indentation (ASTM F1914) **Passes** Resistance to Heat (ASTM F1514) **Passes** Passes Resistance to Light (ASTM F1515) Resistance to Chemicals (ASTM F925) Passes Passes, Class I Radiant Panel (ASTM E648)

Slip Resistance (ASTM D2047) ADA compliant

### Warranties

Commercial Limited Underbed Bond Warranty S150/4151/LokWorx+ Resilient

Resilient 15 Year Commercial Limited

#### Environmental

FloorScore® Certified Indoor Air Quality

Recycled Content Pre-consumer - 30%, Post-consumer - 0%

> Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.





