




938 Charcoal Soapstone




1173 Beige Slate



1174 Ivory Soapstone



5214 Gray Slate



5215 Light Gray Soapstone



5215 Light Gray Soapstone, 938 Charcoal Soapstone

Style Name	OBELISK GLUE DN	
Style Number	5680V	
Construction	Heavy Commercial Luxury Vinyl	
Class / ASTM F1700	Class III Printed Film Vinyl Tile, Type B (embossed)	
Attached Underlayment	No	
Finish	ExoGuard®	
	U.S.	Metric
Nominal Dimensions	12 in w, 24 in l	30.5 cm w, 61 cm l
Actual Dimensions	12 in w, 24 in l	30.48 cm w, 60.96 cm l
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Thickness	0.098 in	2.5 mm
Installation	Direct Glue	
Recommended / Required Adhesive	LokWorx+ (236MM) or S150 (5025M)	

Packaging

Pieces per box	20 pcs	
Area per box	40.05 sq ft	3.72 sq m
Weight per box	39.68 lbs	18 kg

Performance Testing

Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

Commercial Limited Underbed Bond Warranty S150/4151/LokWorx+ Resilient Resilient 15 Year Commercial Limited

Environmental

Indoor Air Quality	FloorScore® Certified
Recycled Content	Pre-consumer - 0%, Post-consumer - 0%

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

