



# PROGROUT PLUS



Merkrete's ProGrout Plus high-performance grout features innovative, patented DUSTLESS Technology (DLT), producing significantly less dust than ordinary thinsets to promote cleaner working conditions and reduce mess. It is creamier and easier to spread.

- ◆ **POLYMER FORTIFIED FOR HARD, DURABLE, PROFESSIONAL RESULTS**
- ◆ **STAIN RESISTANT, COLOR CONSISTENT AND EFFLORESCENCE FREE**
- ◆ **FOR 1/16" (1.5 MM) TO 1/2" (13 MM) GROUT JOINTS**
- ◆ **EASY MIXING — JUST ADD WATER; NO ADDITIVES REQUIRED**
- ◆ **EXCEEDS ANSI A118.7**





# PROGROUT PLUS™



ProGrout Plus is a high-performance, fast-setting, DUSTLESS, color-consistent and efflorescence-free grout providing hard, durable grout joints. ProGrout Plus is approved for grout joints ranging from 1/16" to 1/2" (1.5 mm to 13 mm) in width, eliminating the need for different grout products.

**FAST SETTING, HIGH PERFORMANCE, DUSTLESS GROUT**

- Polymer-fortified for hard, durable, professional results
- Stain resistant, color consistent and efflorescence free
- For 1/16" (1.5mm) to 1/2" (13mm) grout joints
- Easy mixing — just add water; no additives required
- Exceeds ANSI A118.7



25 LBS | 11.3 KGS

PAREXUSA

## STANDARDS:

- Exceeds ANSI A118.7

COVERAGE				
PROGROUT PLUS/INTEGRA/DURACOLOR PER 25-LB. BAG				
NOMINAL TILE SIZE	JOINT WIDTH			
	1/8"	1/4"	3/8"	1/2"
2"x 2"x 1/4"	93	48	33	26
4"x 4"x 3/8"	122	62	42	32
4"x 8"x 3/8"	162	82	55	42
6"x 6"x 3/8"	182	92	62	47
6"x 8"x 3/8"	208	105	70	53
8"x 8"x 3/8"	242	122	82	62
10"x 10"x 3/8"	302	152	102	77
12"x 12"x 3/8"	362	182	122	92
15"x 15"x 3/8"	452	227	152	114
16"x 16"x 3/8"	482	242	162	122
18"x 18"x 3/8"	542	272	182	137
20"x 20"x 3/8"	602	302	202	152

## USES

- Ceramic tile and natural stone applications
- Floors and walls
- Residential and commercial
- Interior and exterior

## ORDERING INFORMATION

Color	Sanded 25 lbs.
BRIGHT WHITE	2573-00010
SNOW WHITE	2573-00011
NAVAJO WHITE	2573-00012
CREAM	2573-00018
CANVAS	2573-00021
TUMBLEWEED	2573-00025
SILVER	2573-00030
LIGHT TAUPE	2573-00032
RIVER ROCK	2573-00034
NATURAL GRAY	2573-00035
GRAY	2573-00038
SANDSTONE	2573-00071
SANTA FE	2573-00150
BUCKSKIN	2573-00153
TRUE TAUPE	2573-00162
DARK CHOCOLATE	2573-00175
TERRACOTTA	2573-00191
BLACK SAPPHIRE	2573-00525

**PAREXUSA**

Parex USA, Inc., a California Corporation

## Corporate Office

2150 Eastridge Ave • Riverside, CA 92507

merkrete.com • 866-516-0061

Tech Support: 800-226-2424

# PROGROUT PLUS

HIGH-PERFORMANCE, DUSTLESS GROUT

- Polymer Modified
- Fast Setting
- DUSTLESS Technology
- Easy Mixing (Just Add Water)
- Exceeds ANSI A118.7



## COVERAGE CHART

Coverage in sq. ft. (m<sup>2</sup>) per 25-lb. (11.34-kg) bag

NOMINAL TILE SIZE	JOINT WIDTH				
	1/16" (1.5 mm)	1/8" (3 mm)	1/4" (6 mm)	3/8" (10 mm)	1/2" (125 mm)
1" x 1" x 1/4" (25 x 25 x 6 mm)	116 (10.8)	58 (5.4)	34 (3.2)	26 (2.4)	22 (2.0)
2" x 2" x 1/4" (50 x 50 x 6 mm)	212 (19.6)	106 (9.8)	58 (5.4)	42 (3.9)	34 (3.2)
4" x 4" x 3/8" (100 x 100 x 10 mm)	272 (25.2)	136 (12.6)	71 (6.6)	49 (4.6)	39 (3.6)
6" x 6" x 3/8" (150 x 150 x 10 mm)	402 (37.4)	201 (18.7)	103 (9.6)	71 (6.6)	55 (5.1)
12" x 12" x 3/8" (300 x 300 x 10 mm)	790 (73.4)	395 (36.7)	201 (18.7)	136 (12.6)	103 (9.6)
18" x 18" x 3/8" (450 x 450 x 10 mm)	1,178 (109.4)	589 (54.7)	298 (27.7)	201 (18.7)	152 (14.1)
24" x 24" x 3/8" (610 x 610 x 10 mm)	1,568 (145.6)	784 (72.8)	395 (36.7)	265 (24.6)	201 (18.7)
6" x 24" x 3/8" (150 x 610 x 10 mm)	636 (59)	318 (29.5)	162 (15.1)	111 (10.3)	85 (7.9)
12" x 24" x 3/8" (300 x 610 x 10 mm)	1,050 (97.6)	525 (48.8)	266 (24.7)	179 (16.6)	136 (12.6)

# ELITE RTU

PREMIUM, READY-TO-USE GROUT

- Ready to Use Straight from Pail
- Resealable; Reusable
- Excellent Stain Resistance
- Easy to Clean and Color Consistent



## COVERAGE CHART

Coverage in sq. ft. (m<sup>2</sup>) per 1-gal. (3.78-l) pail

NOMINAL TILE SIZE	JOINT WIDTH					
	1/16" (1.5 mm)	1/8" (3 mm)	3/16" (4.5 mm)	1/4" (6 mm)	3/8" (10 mm)	1/2" (125 mm)
2" x 2" x 1/4" (50 x 50 x 6 mm)	103 (9.6)	50 (4.7)	33 (3.1)	24 (2.2)	15 (1.4)	11 (1.0)
4-1/4" x 4-1/4" x 1/4" (108 x 108 x 6 mm)	221 (20.5)	109 (10.1)	72 (6.7)	54 (5.0)	35 (3.3)	26 (2.4)
6" x 6" x 1/4" (150 x 150 x 6 mm)	313 (29.1)	155 (14.4)	103 (9.6)	77 (7.2)	50 (4.7)	37 (3.4)
8" x 8" x 3/8" (200 x 200 x 10 mm)	278 (25.8)	138 (12.8)	91 (8.5)	68 (6.3)	45 (4.2)	33 (3.1)
12" x 12" x 3/8" (300 x 300 x 10 mm)	417 (38.7)	208 (19.3)	138 (12.8)	103 (9.6)	68 (6.3)	50 (4.7)
24" x 6" x 3/8" (610 x 150 x 10 mm)	334 (31.0)	166 (15.4)	11 (10.2)	82 (7.6)	54 (5.0)	40 (3.7)
24" x 12" x 3/8" (610 x 300 x 10 mm)	557 (51.7)	278 (25.8)	184 (17.1)	138 (12.8)	91 (8.5)	68 (6.3)

## PAREXUSA

Parex USA Inc., A California Company  
2150 Eastridge Ave.  
Riverside, CA 92507  
www.parexusa.com  
886-516-0061  
Tech Support: 800-226-2424  
©2023, Parex USA, Inc. MK PGPE CC 0423

MERKRETE



# PROGROUT PLUS ELITE RTU



- COLOR CONSISTENT
- STAIN RESISTANT
- EFFLORESCENCE FREE
- FOR GROUT JOINTS 1/16" TO 1/2" (1.5 TO 13 MM)



# GROUT

COLOR SELECTION

Tile size, style, color, composition and areas of use constantly evolve. So must the tile installation products. Using the correct installation products is vital to the success of every tile project and selecting the right grout is just as important.

# GROUT CALCULATOR

[www.merkrete.com/grout\\_calculator.shtml](http://www.merkrete.com/grout_calculator.shtml)

**PGP** ProGrout Plus   **E** Elite RTU   **SC** 100% Silicone Caulk



0010 BRIGHT WHITE **PGP SC**



00011 SNOW WHITE **PGP E SC**



00012 NAVAJO WHITE **PGP E SC**



00018 CREAM **PGP E SC**



00021 CANVAS **PGP E SC**



00025 TUMBLEWEED **PGP E SC**



00030 SILVER **PGP E SC**



00032 LIGHT TAUPE **PGP SC**



00034 RIVER ROCK **PGP E SC**



00035 NATURAL GRAY **PGP E SC**



00038 GRAY **PGP E SC**



00071 SANDSTONE **PGP E SC**



00162 TRUE TAUPE **PGP SC**



00175 DARK CHOCOLATE **PGP E SC**



00150 SANTA FE **PGP E SC**



00153 BUCKSKIN **PGP E SC**



00191 TERRACOTTA **PGP SC**



00525 BLACK SAPPHIRE **PGP E SC**

Sample colors shown are approximate to the final grout color. Final installed grout color may vary due to job conditions, tile porosity, mixing ratio, sealers, installation methods, temperature, or individual batches. Use grouts with the same batch number whenever possible. Different batch numbers should be dry blended together to obtain color uniformity. Follow ANSI A108.10 grouting practices. Please contact Customer Care Department for further questions at 877-547-8822.