

# LAMBERT

## RAINFALL SHOWER HEAD

SKU: 926430, 926447

### BEFORE YOU BEGIN

We recommend consulting a professional if you are unfamiliar with installing plumbing fixtures. Signature Hardware accepts no liability for any damage to the faucet, plumbing, sink, counter top, or for personal injury during installation.


Observe all local plumbing and building codes.

Unpack and inspect the product for shipping damage. If any damage is found, contact our Customer Relations team at 1-855-715-1800.

### GETTING STARTED

Ensure that you have gathered all the required materials that are needed for the installation.

### TOOLS AND MATERIALS:



Groove Joint Plier



Adjustable Wrench



Dry Cloth



Plumbers Tape



Phillips  
Screwdriver



Damp Cloth



Silicone Sealant  
(100% Neutral Cure)

For Warranty information, please visit: [signaturehardware.com/services/warranty](https://signaturehardware.com/services/warranty)

REVISED 10/27/2020  
CODES: 515410, 515411, 515409, 515416  
515417, 515415, 515413, 515412, 515414  
515429, 515428, 515430, 515425, 515426  
515424, 515422, 515421, 515423, 515419  
515420, 515418, 515435, 515436, 515434  
515432, 515433, 515431

### INSTALLATION

1. Apply plumber's tape to the threads on both ends of the shower arm and slide on the decorative escutcheon.

2. Insert the new arm into the fitting in the wall or ceiling and twist to tighten. Finish tightening with your adjustable wrench. Wrap a dry cloth around the shower arm to protect the finish while tightening with adjustable wrench.

**Note:** If your shower head does not feature a shower arm, connect the shower head directly to the fitting in the wall or ceiling.

3. Thread the new shower head onto the arm and hand-tighten. Hold the shower arm in place with groove joint pliers and finish tightening the shower head with your adjustable wrench. Wrap both in a dry cloth to protect the finish.

4. Before securing the decorative escutcheon to the wall, turn on the water supply to make sure that all connections are tight and there is no leaking. If no leaks are detected, continue with the installation. If leakage does occur, use your adjustable wrench to tighten the connections as necessary. If problems persist, contact Customer Service at 1-866-855-2284.

5. Apply a bead of silicone sealant to the back of the escutcheon and press firmly into place against the installation surface. Wipe away any excess sealant with your damp cloth.

6. Install the handle faceplate with the installation hardware.

7. Make sure the valve is in the OFF position and install your shower handle. Tighten the set screw in the middle or side of the handle to secure the handle in place.