



SURFACE BOLT

INSTALLATION INSTRUCTIONS

Before you begin, read the installation instructions below. Observe all local building and safety codes.

Unpack and inspect the product for any shipping damages and ensure that none of the required pieces are missing. If you find damages, do not install. Contact Customer Service at 1.866.855.2284. If you need assistance or have questions while installing your surface bolt, contact Customer Service.

We recommend consulting a professional if you are unfamiliar with installing hardware fixtures. Signature Hardware accepts no liability for any damage to the bolt or door, or for personal injury during installation.

TOOLS AND MATERIALS:

Tape measure

Pencil

Drill

SURFACE BOLT INSTALLATION

1. Determine the bolt mounting location. Most surface bolts include hardware for mounting to the top or the bottom of the door.
2. Hold the bolt 1/2"-3/8" from the edge of the door when retracted. If your bolt has concealed screw holes (**A**), slide the bolt to expose the holes and use a pencil to mark the hole locations. If your bolt has guides (**B**), place the bolt on the door with the guides in position and use a pencil to mark the hole locations.
3. Drill pilot holes in the locations marked in the previous step.
4. Secure the bolt to the door with the provided mounting hardware.
5. Hold the end guide (**C**) in place at the top of the door frame or on the floor and mark the hole locations.
6. Drill pilot holes in the locations marked in the previous step.
7. Secure the end guide to the floor or door frame with the provided mounting hardware.

