



# SURFACE-MOUNT POCKET DOOR PULL INSTALLATION

## BEFORE YOU BEGIN

We recommend consulting a professional if you are unfamiliar with installing this type of hardware. Signature Hardware accepts no liability for any damage to the product, door, home, or for personal injury during installation.

Observe all local building codes.

Unpack and inspect the product for shipping damage. If any damage is found, contact our Customer Relations team at 1-855-715-1800.

---

## GETTING STARTED

- Ensure that you have gathered all the required materials that are needed for the installation.

---

## TOOLS AND MATERIALS:



Phillips  
Screwdriver



Jigsaw



Chisel



Pencil



Hammer

## INSTALLATION

1. Place the door pull at the desired installation location. **Tip: Standard height for hardware installation is 36" from the bottom of the door.**
2. Mark the location of the pull on the door using a pencil. Outline the entire pull. Measure the portion of the pull that will be recessed into the door, then mark the location of the recessed portion on the door.
3. Use a chisel and hammer to remove wood from the door at the marked installation location. If necessary, use a jigsaw to create a hole for the recessed portion of the pull.
4. Test fit the door pull at the prepared installation location. If the pull does not sit properly, make adjustments to the area using the chisel and/or jigsaw.
5. Once the area is prepared and the door pull fits properly, attach the pull to the door. Use the provided hardware to secure the pull to the door.