



## CUP PULL

### BEFORE INSTALLING

Before installing, read entire cup pull installation instructions. Observe all local building and safety codes. For the following installation instructions it is assumed that any old fixtures have been removed and any repairs to the drawer or door have been completed.

### INSTRUCTIONS

Unpack and inspect the product for any shipping damages. If you find damages, do not install. Contact Customer Service at 1.855.715.1800. If you need assistance or have questions while installing your cup pull contact Customer Service.

We recommend consulting a professional if you are unfamiliar with installing hardware fixtures. Signature Hardware accepts no liability for any damage to the drawer or cabinet, for personal injury during installation.

The most common hole spacings for drawer pulls are 2-1/2", 3" and 4". If you are replacing drawer pulls new holes may need to be drilled.

### TOOLS AND MATERIALS:



Tape Measure



Drill



Safety Glasses



Pencil



Painter's Tape



Level



Screwdriver

### IMPORTANT INFORMATION

1. Use a tape measure to find the center of the drawer if installing only one pull, or divide the drawer into the appropriate sections if installing multiple pulls.
2. Use painter's tape to mark the pull locations.
3. Mark the exact position of the pull on the painter's tape. Use a level to make sure that the marks are horizontal.
4. Drill mounting holes in the locations marked in the previous step. Remove the painter's tape when all holes have been drilled.
5. Attach the pulls to the drawers with the provided mounting hardware.