SIMPLY CONSERVE

OVERVIEW

This LED T8 lamp is a perfect plug-and-play solution to convert existing fluorescent fixtures to LED. Designed to deliver 1800 lumens, these lamps produce the same light output as a 32W fluorescent with less than half the power. The glass construction provides a strong, quick, and safe installation without any re-wiring of the ballast or fixture. Compatible with most electronic instant-start and programmed rapid-start T8 ballasts.

KEY FEATURES

- Operation temperature: -4°F 113°F
- Storage temperature: -40°F 185°F
- THD: 20%
- Ignition time: <1.0 second
- Easy retrofit into most common linear fluorescent fixtures
- Compatible with most electronic instant-start ballasts
- Product is rated for indoor use only



	Туре
Catalog #	
Project	
Comments	Date
Prepared by	







Yea

ORDERING INFORMATION

SOURCE	LAMP WATTAGE	LAMP TYPE	MATERIAL	ССТ	OPERATION
L = LED	11 = 11W 14 = 14W	T8 = T8 Tube	G = Glass	40 = 4000K 50 = 5000K	A = UL Type A



SIMPLY CONSERVE

LED T8 TYPE A L11T8G40A, L11T8G50A, L14T8G40A, L14T8G50A


SPECIFICATIONS

ITEM #	LAMP WATTS	EFFICACY	ССТ	LUMENS	CRI	VOLTAGE	PF	HZ	DIM
L11T8G40A	11W	163 lm/W	4000K	1800	≥80	BALLAST- DEPENDENT	≥0.9	50/60	No
L11T8G50A	11W	163 lm/W	5000K	1800	≥80	BALLAST- DEPENDENT	≥0.9	50/60	No
L14T8G40A	14W	157 lm/W	4000K	1800	≥80	≥80 BALLAST- DEPENDENT		50/60	No
L14T8G50A	14W	157 lm/W	5000K	1800	≥80	BALLAST- DEPENDENT	≥0.9	50/60	No

DIMENSIONS



CASE



CATALOG #	DIAMETER	L	CATALOG #	L	W	Н	CASE QTY	GROSS WT
L11T8G40A	1"	48"	L11T8G40A	49"	6.3"	5.9"	25	13 lbs.
L11T8G50A	1"	48"	L11T8G50A	49"	6.3"	5.9"	25	13 lbs.
L14T8G40A	1"	48"	L14T8G40A	49"	6.3"	5.9"	25	13 lbs.
L14T8G50A	1"	48"	L14T8G50A	49"	6.3"	5.9"	25	13 lbs.

5-Year Limited Warranty



If this lamp fails to operate for a 5-year period under normal consumer use (6 hours/day, 7 days/week), from the date of purchase or distribution by an energy conservation program and has been properly installed with a compatible ballast, AM Conservation Group will replace the lamp free of charge.

For warranty claims, please contact:

customercare@amconservationgroup.com

To learn more, please visit:

www.amconservationgroup.com



1701 Charleston Regional Parkway, Suite A | Charleston, SC 29492 (843) 971-1414 | www.amconservationgroup.com