

L12PL40G24QH, L12PL50G24QH

OVERVIEW

This plug-and-play lamp offers a simple and efficient lighting solution for task lighting. Its mercury-free, and is ideal for brightly illuminating spaces without overpowering them. A 50,000-hour lifespan means less bulb replacement, and DLC certification guarantees energy and money savings.

0	Туре
Catalog #	
Project	
Comments	Date
Comments	
Prepared by	

KEY FEATURES

- Operation temperature: -4°F 104°F
- Storage temperature: -4°F 104°
- THD: 20%
- Target replacement: 26W/G24Q or GX24Q
- Direct replacement/Ballast compatible: New or existing ballast is required for operation
- Target replacement: 18W/7T4/G24Q
- Shatter-resistant
- Mercury-free









INSTANT-ON



HORIZONTAL INSTALLATION



BEAM **ANGLE**



50,000 **HOURS**











ORDERING INFORMATION

SOURCE	WATTAGE	LAMP TYPE	BASE	CCT	ORIENTATION
L = LED Linear	12 = 12W	PL = PL Lamp	G24Q/GX24Q	40 = 4000K 50 = 5000K	H = Horizontal

^{*}See ballast compatibility chart at www.amconservationgroup.com




L12PL40G24DH, L12PL50G24DH

SPECIFICATIONS


CATALOG #	WATTS	EFFICACY	CCT	LM	CRI	VOLTAGE	PF	HZ	DIM
L12PL40G24QH	12W	91 lm/W	4000K	1100 lm	≥80	120-277V	≥0.9	60 Hz	No
L12PL50G24QH	12W	91 lm/W	5000K	1100 lm	≥80	120-277V	≥0.9	60 Hz	No

DIMENSIONS

PRODUCT



CASE



CATALOG #	L	w	BASE
L12PL40G24QH	6 1/16"	1 23/64"	G24Q, GX24Q
L12PL50G24QH	6 1/16"	1 23/64"	G24Q, GX24Q

L	W	Н	CASE QTY	GROSS WT
9 1/2"	15 5/16"	7 5/16"	60	12 3/4 lb.
9 1/2"	15 5/16"	7 5/16"	60	12 3/4 lb.

5 -Year Limited Warranty



If this PL lamp fails to operate for a 5-year period under normal consumer use (6 hours/day, 7 days/week), from the date of purchase or distribution by an energy conservation program and has been properly installed, AM Conservation Group will replace the lamp free of charge.

For warranty claims, please contact:

customercare@amconservationgroup.com

To learn more, please visit:

www.amconservationgroup.com

