


2023 Technical Data Sheet

Available Items Specs




SkyOutlet

Weight Supporting Ceiling Receptacle

Specs:

SkyOutlet - Weight Supporting Ceiling Receptacle (WSCR) - designed to mate with SkyPlug Weight Supporting Attachment Fitting (WSAF) to provide electrical power and secure mounting for luminaires and other electrical equipment.

Permitted by **NEC**
ANSI/NEMA WD 6-2021
UL498




Commercial Applications

Residential Home Builder
Property Development / Multi-tenant
Hospitality
Retail

Code

NEC 2017, Article 314.27, recognizes new technology designed to power and support luminaires from a receptacle and mounting means located in or mounted directly to the box




Mounted in Junction Box

Features & Benefits:

- Easy-to-install Code compliant mounting & coupling system
- Visual color-coding aid on SkyOutlet to ensure proper wiring connection
- Low-profile for maximum wiring room in junction box, Min. size 4" x ½" outlet box.
- Meets UL 498 and CSA C22.2 No 42 Finger-Probe safety requirements
- Flame Retardent Casing Rated at 130 degrees C
- Accepts No. 12 and No. 14 AWG solid wire
- Side-wire terminal with screw taps for maximum conductivity and wire retention

- Electrical contact points are copper coated with Nickel plating for corrosion-resistance and wear protection
- Certified for Luminaire Support 50 Lbs. Max.
- Meets UL 514A Fixture/Luminaire Studs pull test with 200lb static load
- UL / cUL Listed (File # E256356)
- CE Certified
- Compliant with 2017 NEC, Article 314.27, 422.33, Article 100 definition
- 1 Year Limited Product Warranty



Units in MM

"Mating System" - Must use in combination with compatible SkyOutlet mounting support

Model	Description	Electrical Ratings	Contacts	Contact Description
SR-3L	Receptacle	125 Vac, 15A	3	L1, L2, Neutral, Ground


SkyPlug

Weight Supporting Attachment Fitting

Specs:

SkyPlug - Weight Supporting Attachment Fitting (WSAF) - designed to mate with corresponding SkyOutlet - Weight Supporting Ceiling Receptacle (WSCR) to provide electrical power and secure mounting for luminaires and electrical devices. SkyPlug devices are factory assembled into electrical equipment for simple and safe ceiling or wall plug-in installations.

Permitted by **NEC**
ANSI/NEMA WD 6-2021
UL498



Commercial Applications

Residential Home Builder
Property Development / Multi-tenant
Hospitality
Retail

Code

NEC 2017, Article 314.27, recognizes new technology designed to power and support luminaires from a receptacle and mounting means located in or mounted directly to the box




Light Fixture
With SkyPlug

Features & Benefits:

- Stainless steel 303 single push-pin actuation for quick release of luminaires
- Inner teeth allow for 360 degree alignment and locking position on SkyOutlet
- Screw-Based wire termination for maximum conductivity and wire retention
- 1/2-20 threaded rod for securing luminaires
- Slotted/phillips combo screws for flexibility in field
- Dry or damp location use
- UL File #E306210

- Brass electrical contact rings with Nickel plating to provide corrosion resistance protection
- Side-wire termination, accepts No.18 & No.20 AWG stranded wire
- Suitable for Luminaire support Max. 50 lbs.
- Double locking mechanism
- Tested to 200 lbs static load
- Universal application for assembly to wall or ceiling mounted luminaires
- CE Certified



“Mating System”- Must use in combination with compatible SkyOutlet mounting support

“Standard Canopy” - Center hole diameter minimum 13mm and height minimum 20mm

Model	Description	Electrical Ratings	# Rings	Mating SkyOutlet
SPU-3L	Luminaire Plug	12V, 10A, 1200 Watts	L1 Live, Neutral, Ground	SR-3L, SR-4L, SR-4F


SkyPlug

Plug & Play Kit For Light Fixtures

Specs:

SkyPlug - Weight Supporting Attachment Fitting (WSAF) - designed to mate with corresponding SkyOutlet - Weight Supporting Ceiling Receptacle (WSCR) to provide electrical power and secure mounting for luminaires and electrical devices. SkyPlug devices are factory assembled into electrical equipment for simple and safe ceiling or wall plug-in installations.

Permitted by **NEC**
ANSI/NEMA WD 6-2021
UL498 UL1598



Commercial Applications

Residential Home Builder
Property Development / Multi-tenant
Hospitality
Retail

Code

NEC 2017, Article 314.27, recognizes new technology designed to power and support luminaires from a receptacle and mounting means located in or mounted directly to the box



Light Fixture
With SkyPlug




Finials And Adaptors

Features & Benefits:

- Stainless steel 303 single push-pin actuation for quick release of luminaires
- Inner teeth allow for 360 degree alignment and locking position on SkyOutlet
- Screw-Based wire termination for maximum conductivity and wire retention
- 1/2-20 threaded rod for securing luminaires
- Slotted/phillips combo screws for flexibility in field
- Dry or damp location use
- SkyPlug UL File #E306210
- Listed Luminaire Fitting E239007

- Brass electrical contact rings with Nickel plating to provide corrosion resistance protection
- Side-wire termination, accepts No.18 & No.20 AWG stranded wire
- Suitable for Luminaire support Max. 50 lbs.
- Double locking mechanism
- Tested to 200 lbs static load
- Universal application for assembly to wall or ceiling mounted luminaires
- CE Certified



“Mating System”- Must use in combination with compatible SkyOutlet mounting support

“Standard Canopy” - Center hole diameter minimum 13mm and height minimum 20mm

Model	Description	Electrical Ratings	# Rings	Mating SkyOutlet
SPU-3L	Luminaire Plug	120V, 10A, 1200 Watts	L1 Live, Neutral, Ground	SR-3L, SR-4L, SR-4F

SkyPlug Smart

SmartPlug & Play Kit For Light Fixtures

Specs:

SkyPlug - Weight Supporting Attachment Fitting (WSAF) – designed to mate with corresponding SkyOutlet Weight Supporting Ceiling Receptacle (WSCR) to provide electrical power and secure plug-in mounting for luminaires. SkyPlug Smart devices are designed to fit into luminaires for simple and safe ceiling installations.

Permitted by **NEC**
ANSI/NEMA WD 6-2021
UL498 UL1472 UL1598



Light Color Changing Modes



Smart features

- Phone
- Voice Control
- Scheduling
- Eco - Energy Saving Mode
- Dimming
- Backup Light
- Ambiance Color Changing
- Night Light
- Power Meter
- Grouping Control Mode



Light fixture With Smart Controller






Finials And Adaptors

Features & Benefits:

- Stainless steel 303 single push-pin actuation for quick release of luminaires
- Inner teeth allow for 360 degree alignment and locking position on SkyOutlet
- Screw-Based wire termination for maximum conductivity and wire retention
- 1/2-20 threaded rod for securing luminaires
- Slotted/phillips combo screws for flexibility in field
- Dry or damp location use
- For AC fixtures only
- Not for use with dimmer switches
- UL Luminaire Fitting E239007

- Brass electrical contact rings with Nickel plating to provide corrosion resistance protection
- Side-wire termination, accepts No.18 & No.20 AWG stranded wire
- Suitable for Luminaire support Max. 50 lbs.
- Double locking mechanism
- Tested to 200 lbs static load
- Smart features include phone control, voice control, dimming, scheduling, RGB changing ring light, back up white “emergency” light
- UL File #E306210
- Smart Controller E506538



“Mating System”- Must use in combination with compatible SkyOutlet mounting support

“Smart Canopy” - Center hole diameter minimum 25.5mm Height minimum 41.5mm

Commercial Applications

Residential Home Builder
Property Development / Multi-tenant
Hospitality
Retail

Code

NEC 2017, Article 314.27, recognizes new technology designed to power and support luminaires from a receptacle and mounting means located in or mounted directly to the box

Model	Description	Electrical Ratings	# Rings	Mating SkyOutlet
0252	Smart Controller	120V, 2A, 240W, 1A LED	3-L1 Live, Neutral, Ground	SR-3L, SR-4L, SR-4F

SkyPlug Smart

Smart Plug & Play Controller For Light Fixtures

Specs:

SkyPlug - Weight Supporting Attachment Fitting (WSAF) – designed to mate with corresponding SkyOutlet Weight Supporting Ceiling Receptacle (WSCR) to provide electrical power and secure plug-in mounting for luminaires. SkyPlug Smart devices are designed to fit into luminaires for simple and safe ceiling installations.

Permitted by **NEC**
ANSI/NEMA WD 6-2021
UL498 UL1472



Smart features

- Phone
- Voice Control
- Scheduling
- Eco - Energy Saving Mode
- Dimming
- Backup Light
- Ambiance Color Changing
- Night Light
- Power Meter
- Grouping Control Mode






Light Fixture
With Smart Controller

Features & Benefits:

- Stainless steel 303 single push-pin actuation for quick release of luminaires
- Inner teeth allow for 360 degree alignment and locking position on SkyOutlet
- Screw-Based wire termination for maximum conductivity and wire retention
- 1/2-20 threaded rod for securing luminaires
- Slotted/phillips combo screws for flexibility in field
- Dry or damp location use
- For AC fixtures only
- Not for use with dimmer switches
- Smart Controller E506538

- Brass electrical contact rings with Nickel plating to provide corrosion resistance protection
- Wire terminal, accepts No.18 & No.20 AWG stranded wire
- Suitable for Luminaire support Max. 50 lbs.
- Double locking mechanism
- Tested to 200 lbs static load
- Smart features include phone control, voice control, dimming, scheduling, RGB changing ring light, back up white “emergency” light
- Smart Plug UL File #E306210



“Mating System”- Must use in combination with compatible SkyOutlet mounting support

“Smart Canopy” - Center hole diameter minimum 25.5mm Height minimum 41.5mm

Commercial Applications

Residential Home Builder
Property Development / Multi-tenant
Hospitality
Retail

Code

NEC 2017, Article 314.27, recognizes new technology designed to power and support luminaires from a receptacle and mounting means located in or mounted directly to the box

Model	Description	Electrical Ratings	# Rings	Mating SkyOutlet
0252	Smart Controller	120V, 2A, 240W, 1A LED	3-L1 Live, Neutral, Ground	SR-3L, SR-4L, SR-4F



SKYX
PLATF O R M S
1-855-SkyPlug | SkyPlug.com
All rights reserved ©

Follow us:

