

### 4-3/4" 121 mm 1" IPS Supply DN 25 mm Finished C/I Wall OF FIXTURE 1-1/2" 38 mm 1-1/2" 38 mm Opening in Wall F-22-A 178 mm 1" I.P.S. OUTLET DN 25 mm Finished Floor

NOTE: Flush Connections shown in dotten lines not included

# Royal 650-ESM

## MICRO Plumb® PRODUCTS Electronic Prison Flushometer

#### **Description**

Concealed water closet flushometer -1" I.P.S. outlet, for bowls and Eastern squat toilets.

#### Flush Cycle

- ☐ Model 650 Water Saver (3.5 gpf/13.2 Lpf)
- ☐ Model 650-2.4 (2.4 gpf/9.0 Lpf)
- ☐ Model 650-1.6 Low Consumption (1.6 gpf/6.0 Lpf)

#### **Specifications**

Quiet, concealed, diaphragm-type, rough brass closet flushometer for either left or right hand supply with the following features:

- 1" I.P.S. WheEL-Handle Bak-Chek® Angle Stop
- Adjustable Tailpiece
- Vacuum Breaker
- 1" Female I.P.S. union Outlet (no flush connection)
- High Copper, Low Zinc Brass Castings for Dezincification Resistance
- Low Consumption flush accuracy controlled by Para-Flo® Technology
- Handle Packing, Stop Seat and Vacuum Breaker Molded from PERMEX® Rubber Compound for Chloramine Resistance

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.





Water Connects Us™

Headquarters • 10500 Seymour Avenue • Franklin Park, IL 60131 P: 847-671-4300 / 800-9-VALVE-9 • F: 847-671-4380 / 800-447-8329