MCR-215 07-14





EL-462-A



ETF-492-A



ETF-458-A EL-154



24 VAC 28-1/2" REF Controller 724 mm 24 VAC 4" x 4" x 2-1/4" Solenoid Electrical 3/8" NPTF Junction Box NOT INCLUDED Tempered Water Supply Furnished 48" for Adults by Others 1219 mm for Adults 42" for Juveniles 1067 mm for Juveniles Finished Wall

Finished Floor

MCR-215

MICRO Plumb® PRODUCTS Infrared Shower Control

Description

Infrared sensor-activated, electronic shower control for a single, pre-mixed shower. System includes six components: ETF-492-A, EL-154, MCR-139-A, ETF-458-A, EL-462-A and AC-11.

Specifications

- Infrared sensor module, controller, solenoid, 120 VAC/24 VAC transformer, 20' power cord kit and mounting hardware for sensor and controller
- Water-proof (NEMA 6) sensor module
- Operates on 24 VAC
- Visible LED target detection
- Adjustable sensing range
- Adjustable run time
- 24 VAC brass body solenoid with integral "Y" strainer
- · Diagnostic LED indicators in control module
- Control module may be located remotely as far as 35' from sensor using additional MICRO Plumb® extension cord kits
- RJ-11 modular connections from sensor and solenoid to controller
- AC-11 Act-O-Matic® self-cleaning shower head with thumb screw volume control

Accessories

ETF-1003-72
ETF-1003-108
ETF-1003-240
ETF-1003-240
ETF-1003-600
EXTENSION Cord Kit
ETF-1003-600





Water Connects Us™

Headquarters • 10500 Seymour Avenue • Franklin Park, IL 60131 P: 847-671-4300 / 800-9-VALVE-9 • F: 847-671-4380 / 800-447-8329