MCR-216

MICRO Plumb[®] PRODUCTS Infrared Shower Control

Description

Infrared sensor-activated, electronic shower control for a single, pre-mixed shower. System includes six components: ETF-492-A, EL-154, MCR-139-A, ETF-458-A, EL-462-A and AC-450.

Specifications

- Infrared sensor module, controller, solenoid, 120 VAC/24 VAC transformer, 20' power cord kit and mounting hardware for sensor and controller
- Water-proof (NEMA 6) sensor module
- Operates on 24 VAC
- Visible LED target detection
- Adjustable sensing range
- Adjustable run time
- 24 VAC brass body solenoid with integral "Y" strainer
- Diagnostic LED indicators in control module
- Control module may be located remotely as far as 35' from sensor using additional MICRO Plumb® extension cord kits
- RJ-11 modular connections from sensor and solenoid to controller
- AC-450 Act-O-Matic® self-cleaning institutional-style shower head

Accessories

• ETF-1003-72

• ETF-1003-600

- 6' Single Wire Extension Cord Kit
- ETF-1003-108 • ETF-1003-240
- 9' Single Wire Extension Cord Kit 20' Single Wire Extension Cord Kit
- 50' Single Wire Extension Cord Kit
- MCR-139-A EL-462-A ETF-492-A ETF-458-A EL-154 AC-450 24 VAC Transformer Controller 11 28-1/2" REF 724 mm 24 VAC 11 4" x 4" x 2-1/4" Solenoid Electrical 3/8" NPTF Junction Box NOT INCLUDED 11 Sensor Tempered Water Supply Furnished 48" for Adults by Others 1219 mm for Adults 42" for Juveniles 1067 mm for Juveniles Finished Wall







Water Connects Us™

Headquarters • 10500 Seymour Avenue • Franklin Park, IL 60131 P: 847-671-4300 / 800-9-VALVE-9 • F: 847-671-4380 / 800-447-8329

The information contained in this document is subject to change without notice.