



Sensor Exposed Flushometer for Floor Mount or Wall Hung Water Closets, 11.5" Rough in



ASME



\*Compliances may change based on options selected.

### Features

- State-of-the-art photovoltaic technology delivers solar operation
- Sensor assembly is powered by a solar cell that will harvest power from artificial indoor light (incandescent, fluorescent or LED) and use it as the energy source
- Batteries provide back-up energy
- Dual-flush model automatically initiates a 1.1 gpf or 1.6 gpf flush based on how long user remains in sensor range
- Operates by means of an infrared sensor with multiple-focused, lobular sensing fields for high and low target detection
- User-friendly, three-second flush delay
- Override button enables manual flushing if sensor's power source fails
- High copper, low zinc brass castings for dezincification resistance
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

### Finishes

- Polished Chrome
- Brushed Stainless
- Polished Brass
- Brushed Nickel
- Polished Chrome

### Flush Volume

- 1.28 gpf for Toilet
- 1.6 gpf / 1.1 gpf for Toilet
- 1.6 gpf for Toilet

### Variations

- TP - Trap Primer
- E - Straight Stop Variation
- GJ - Ground Joint Stop
- YO - Angle Stop Bumper
- YG - Angle Stop Extended Bumper
- YH - Single Wall Bumper
- YI - Double Wall Bumper
- OR - Override Button
- YJ - Split Ring Pipe Support
- YK - Solid Ring Pipe Support
- YL - Split Ring with Seat Bumper Pipe Support
- XYV - Valve Less Vacuum Breaker
- O - Offset Vacuum Breaker
- W - 3/4 inch Flush Connection
- AFD - Anti-Flood Device
- DFB - Dual Filtered Bypass Diaphragm
- WWT - Whitworth Thread