Crown® II Model Flushometer

120

Description

Exposed, Water Closet Flushometer for floor mounted back spud bowls. Valve cannot be converted to exceed a low consumption flush.

Flush Cycle

☐ Model 120-1.6 Low Consumption (1.6 gpf/6.0 Lpf)

Specifications

Quiet, Exposed, Piston Type, Chrome Plated Closet Flushometer with the following features:

- Fixed Volume Piston with Filtered O-ring Bypass
- ADA Compliant Metal Oscillating Non-Hold-Open Handle with Triple Seal Handle Packing
- Aesthetically contoured Cover, Handle Socket and Flanges
- Aesthetic Cover and Handle Accent Rings supplied in contrasting Special Finish
- 1" I.P.S. Screwdriver Bak-Chek™ Angle Stop
- Locking Vandal Resistant Stop Cap
- Adjustable Tailpiece
- High Back Pressure Vacuum Breaker Flush Connection with One-piece Bottom Hex Coupling Nut
- Elbow Flush Connection, Spud Coupling and Flange for 11/2" Back Spud
- Sweat Solder Adapter with Cover Tube and Cast Set Screw Wall Flange
- High Copper, Low Zinc Brass Castings for Dezincification Resistance
- Valve designed to accept Low and Ultra-Low Consumption Pistons only to ensure Water Conservation
- Non-Hold-Open Handle, Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Handle Packing, Main Seat, Stop Seat and Vacuum Breaker to be molded from PERMEX™ Rubber Compound for Chloramine Resistance

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037, ANSI/ASME 112.19.6, and Military Specification V-29193.

Special Finishes

| □ PB | Polished Brass (PVD Finish) |
|------|-----------------------------|
| □ GP | Gold Plate (PVD Finish) |
| □ BN | Brushed Nickel (PVD Finish) |
| □ SF | Satin Chrome |

Cover and Handle Accent Rings supplied in Polished Brass unless specified otherwise.

See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.



| This space for Architect/Engineer approval | | |
|--|----------|--|
| Job Name | Date | |
| Model Specified | Quantity | |
| Variations Specified | | |
| Customer/Wholesaler | | |
| Contractor | | |
| Architect | | |

The information contained in this document is subject to change without notice.



SLOAN VALVE COMPANY • 10500 SEYMOUR AVE. • FRANKLIN PARK, IL. 60131 Ph: 1-800-9-VALVE-9 or 1-847-671-4300 • Fax: 1-800-447-8329 or 1-847-671-4380 Made in the U.S.A. www.sloanvalve.com



