

# Gem•2® Model Flushometer



## Description

Exposed, Urinal Flushometer for 11/4" top spud urinals.

### Flush Cycle

□ Model 180 (3.0 gpf/11.0 Lpf)

- □ Model 180-1.5 Water Saver (1.5 gpf/5.7 Lpf)
- □ Model 180-1.0 Low Consumption (1.0 gpf/3.8 Lpf)

#### Specifications

Quiet, Exposed, Piston Type, Chrome Plated Urinal Flushometer with the following features:

- Fixed Volume Piston with Filtered O-ring Bypass
- ADA Compliant Metal Oscillating Non-Hold-Open Handle
- 1" I.P.S. Screwdriver Bak-Chek® Angle Stop
- Locking Vandal Resistant Stop Cap
- Adjustable Tailpiece
- Vacuum Breaker Flush Connection
- Spud Coupling, Wall and Spud Flanges for 11/4" Top Spud
- High Copper, Low Zinc Brass Castings for Dezincification Resistance
- Non-Hold-Open Handle and No External Volume Adjustment to Ensure Water Conservation
- Handle Packing, Stop Seat and Vacuum Breaker Molded from PERMEX<sup>™</sup> Rubber Compound for Chloramine Resistance

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037, ANSI/ASME A112.19.2, and Military Specification V-29193.

#### Variations

□ T 1½" Flush Connection and Spud Coupling
--

□ YB	Sweat Solder Adapter Kit
	Less Vacuum Breaker

□ YBYC Sweat Solder Adapter & Cast Wall Flange with Set Screw

Note: Bak-Chek<sup>®</sup> Angle Stop available with 1" Whitworth Thread (please specify).

See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.

This space for Architect/Engineer approval		
Job Name	Date	
Model Specified	Quantity	
Variations Specified		
Customer/Wholesaler		
Contractor		
Architect		
The information contained in this do	ocument is subject to change without notice.	



DAN

 SLOAN VALVE COMPANY • 10500 SEYMOUR AVE. • FRANKLIN PARK, IL. 60131

 Ph: 1-800-9-VALVE-9 or 1-847-671-4300
 • Fax: 1-800-447-8329 or 1-847-671-4380

 Made in the U.S.A.
 www.sloanvalve.com