

Above Deck Water **Temperature Control Valve**

Description

Above Deck Manual Water Temperature Control Valve for use with Sloan OPTIMA® Sensor Operated Faucets.


Model

☐ Model MIX-100-A, Optimix® Valve — Stand Alone ☐ Model MIX-110-AA, Optimix® Valve and Trim Plate Model MIX-110-AA is only available with Sloan Optima and Optima Plus Faucets that are specified with the "ADM" (Above-Deck-Mixer) variation.

Specifications

- All Metal Valve Body with Ceramic Cartridge
- ADA Compliant Lever Handle with Hot and Cold Position Indicators
- Flexible Supply Line with 3/8" Compression Fittings (for connection to spout)
- Integral Check Valves Located in Inlets of Hot and Cold Supply Fittings
- Hot Water Temperature Limit Stop
- Mounting Hardware and Installation Instructions

Trim Plate is supplied with the Optimix Valve when furnished with the faucet as the "ADM" (Above-Deck-Mixer) variation. Trim Plates are available for both 4" (102 mm) and 8" (203 mm) centerset spread lavatories. The "ADM" variation is available with most Sloan Optima and Optima Plus faucet models. Consult the faucet specification sheets to determine the availability of this and other mixing options.



† The above rough-ins are representative of a typical Optimix installation. Installation may vary slightly depending on the model of Sloan Faucet used. See Faucet Specification Sheet for more information.








SLOAN VALVE COMPANY • 10500 SEYMOUR AVE. • FRANKLIN PARK, IL. 60131 Phone: 1-800-9-VALVE-9 or 1-847-671-4300 • Fax: 1-800-447-8329 or 1-847-671-4380 http://www.sloanvalve.com

Optima MIX-100-A & MIX-110-AA S.S. — Rev. 0 (08/01) Copyright © 2001 SLOAN VALVE COMPANY

Made in the U.S.A.

Printed in the U.S.A.





This space for Architect/Engineer approval	
Job Name	Date
Model Specified	Quantity
Variations Specified	
Customer/Wholesaler	
Contractor	
Architect	