

(121mm) (254mm) 10" 1" I.P.S **SUPPLY** (DN 25mm) "L" DIM. 23/4" (70mm) + WALL THICKNESS CENTERLINE 1¹/2" (38mm) OPENING OF FIXTURE IN WALL 101/2" (51mm) (267mm) **OPENING** IN WALL 9" (229m CENTERLINE OF WASTE FIN. **FLOOR** WALL

Regal 144 S.S. — Rev. 1 (12/01)
Copyright © 2001 SLOAN VALVE COMPANY Printed in the U.S.A.

Regal[®] Model Flushometer



Description

Concealed Water Closet Flushometer, for wall hung back spud bowls.

Flush Cycle

- ☐ Model 144 Water Saver (3.5 gpf/13.2 Lpf)
- ☐ Model 144-1.6 Low Consumption (1.6 gpf/6.0 Lpf)

Specifications

Quiet, Concealed, Diaphragm Type, Rough Brass Closet Flushometer for either left or right hand supply with the following features:

- ADA Compliant Metal Oscillating Non-Hold-Open Handle
- 1" I.P.S. Wheel Handle Bak-Chek™ Angle Stop
- Adjustable Tailpiece
- Vacuum Breaker
- Elbow Flush Connection and Spud Coupling for 1½" Concealed Back Spud
- Exposed Parts Chrome Plated
- High Copper, Low Zinc Brass Castings for Dezincification Resistance
- Non-Hold-Open Handle and No External Volume Adjustment to Ensure Water Conservation
- Low Consumption flush accuracy controlled by Para-Flo™ Technology
- Handle Packing, Stop Seat and Vacuum Breaker to be Molded from PERMEX™ Rubber Compound for Chloramine Resistance

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037, ANSI/ASME 112.19.6, and Military Specification V-29193.

L Dimension

Specify the "L" Dimension for the proper length of the Handle Assembly and Flush Connection. The "L" Dimension is equal to the Wall Thickness (to the nearest whole inch) plus 2¾" (70 mm).

Variations

\Box TP	Trap Primer Elbow
□ WB	For installation with Sloan Easy Access® Wall Box
□ YB	Sweat Solder Adapter
□ YI	Two Wall Bumpers (for open front seat without cover)

See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.



The information contained in this document is subject to change without houce.



Made in the U.S.A.

SLOAN VALVE COMPANY • 10500 SEYMOUR AVE. • FRANKLIN PARK, IL. 60131 Ph: 1-800-9-VALVE-9 or 1-847-671-4300 • Fax: 1-800-447-8329 or 1-847-671-4380 http://www.sloanvalve.com