

#### Project:

# Thin-Line LED Pendant Spec Sheet


**SKU**: 2816.25-8-J20

One of our best selling families, Thin-Line is a system of minimally scaled LED linear pendants, uplight/downlight wall bars, and indirect light wall bars, Thin-Line is offered in a variety of lengths, finishes, and lighting configurations. Thin-Line Pendants are available in single- and double-sided configurations; the single-sided configurations can be installed as a downlight or up-light, providing direct or indirect illumination. The driver for this fixture must be installed in a remote location. If you would like the look of a smaller canopy than our standard, our Optional Mini Box Canopy is also available for the Thin-Line LED Pendant.

Learn more: https://sonnemanlight.com/thin-line-led-pendant

#### Type #:





#### **Dimensions**

### **Electrical Specs**

Bulb(s) Included?:	Yes
Bulb 1 Type:	Integral LED
Bulb Quantity:	1
Input Voltage:	120VAC
Wattage:	47
Initial Lumens:	3120
Delivered Lumens:	1800
Kelvin:	3000K
CRI:	90
Power Supply Type:	Driver
Power Supply Quantity:	1
Power Supply Location:	Remote
Dimming Type:	TRIAC/ELV
Bulb Max Wattage:	47

#### Installation

 Installation:
 Licensed electrician required

 Cord Length:
 20 ft

 Minimum Hanging Height:
 5.75"

 Maximum Hanging Height:
 245"

#### Shipping

 Carton 1 L x W x H:
 99" X 7" X 4"

 Carton 1 Gross Weight:
 7 LBS

#### Shade

Shade Material: Aluminum w/Optical Acrylic

#### General Listings

Features: Damp Rated
Certification: C-ETL-US
Color/Finish: Satin Black (.25)

## Available Finishes

Available Finishes: Bright Satin Aluminum (.16), Satin Black (.25), Satin White (.03)

#### Available Color Temperatures

Available Color Temperatures: 2700K, 3000K, 3500K